

# VA PROVIDE HIGH LEVEL DISINFECTION ROOM FOR SPS AT SAN JUAN CAMPUS

SAN JUAN, PUERTO RICO  
CONTRACT NO. 36C24822C0087  
DESIGN SERVICES PROJECT: 672-22-810

PROJECT LOCATION: VA CARIBBEAN HEALTHCARE SYSTEM  
10 CALLE CASIA - ADM. BLDG. SUITE 4M456  
SAN JUAN, PR 00921-3201



ISSUING OFFICE:  
DEPARTMENT OF VETERANS AFFAIRS  
NETWORK CONTRACTING OFFICE 8 (NC08)  
CONSTRUCTION TEAM 2  
ANA G. ALVARADO, NCO 8 CONTRACTING OFFICER

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

<div>REVISIONS</div> <table><thead><tr><th>NO.</th><th>DESCRIPTION</th><th>DATE</th></tr></thead><tbody><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr></tbody></table>			NO.	DESCRIPTION	DATE																						<div>CONSULTANT</div>		<div>ARCHITECT/ENGINEER OF RECORD</div> <div>A/E:<div><div>RGD</div><div>CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO</div><div>561-743-0165   407-845-6630</div><div>WWW.RGDENGINEERS.COM</div><div>121 S ORANGE AVE #1230, ORLANDO, FL 32811</div><div>CERT OF AUTH 5454</div></div></div>		<div>STAMP</div> <div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div>LIC. 24629</div><div>EXPIRA</div><div>PUERTO RICO</div></div>		<div>FMS Project and Section</div> <div>VAU.S. Department of Veterans Affairs</div>		<div>Drawing Title</div> <div>COVER SHEET</div> <div>Approved:</div>		<div>Phase</div> <div>CD(100%CD-ISSUE FOR BID)</div> <div>FULLY SPRINKLERED</div>		<div>Project Title</div> <div>VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS</div> <div>Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201</div> <div>Issue Date04/22/2024</div> <div>CheckedRSM</div> <div>DrawnPJG</div>		<div>Project Number</div> <div>672-22-810</div> <div>Building Number</div> <div>1</div> <div>Drawing Number</div> <div>GI-001</div>	
NO.	DESCRIPTION	DATE																																								

A

B

C

D

E

F

SHEET INDEX

Drawing No. Title	
GENERAL	
GI-001	COVER SHEET
GI-002	SHEET INDEX, GENERAL NOTES, SYMBOLS AND ABBREVIATIONS
LS-001	LIFE SAFETY PLAN
LS-002	PROPOSED DEBRIS REMOVAL
ARCHITECTURAL	
AE-101A	DEMO PLAN
AE-101B	PROPOSED FLOOR PLAN
AE-102A	REFLECTED CEILING PLAN
AE-405	INTERIOR ELEVATIONS AND DETAILS
AE-600	PARTITION TYPES, DOOR SCHEDULE AND DETAILS
PLUMBING	
PL-001	PLUMBING COVER SHEET
PL-101	FIRE PROTECTION PLANS
PL-201	PLUMBING PLANS
PL-501	PLUMBING DETAILS AND SCHEDULES
MECHANICAL	
MH-001	MECHANICAL COVER SHEET
MD-101	MECHANICAL DEMOLITION PLAN
MD-102	MECHANICAL PHASING PLAN
MH-101	MECHANICAL FLOOR PLAN
MH-401	MECHANICAL SCHEDULES
MH-501	MECHANICAL DETAILS
ELECTRICAL	
E-001	ELECTRICAL COVER SHEET
EP-101	ELECTRICAL FLOOR PLANS
E-501	ELECTRICAL DETAILS
E-601	PANEL SCHEDULE

ABBREVIATIONS


A	AIR CONDITIONING	CPT	CARPET	FF&E	FURNITURE, FIXTURE, AND EQUIPMENT	KPA	KILOPASCALS	P	PAINT / PUMP / PENDANT	SS	SERVICE SINK / SANITARY SEWER
A/C	ANCHOR BOLT / AIR BLENDER	CR	CRASH RAIL	FH	FIRE HYDRANT	KS	KITCHEN SINK	P	PASCAL	SSM	SOLID SURFACE MATERIAL
AB	ACRYLONITRILE-BUTADIENE-STYRENE	CS	CONCRETE SEALER	FHC	FIRE HOSE CABINET	KV	KILOVOLT	PA	PARTITION	SSO	STORM SEWER OVERFLOW
ABS	ALTERNATING CURRENT / AIR COMPRESSOR	CSF	CUBIC FEET PER SECOND	FIN	FINISH	KVA	KILOVOLT AMPERE	PART	PARALLEL	SST	STAIR TREAD
AC	ADJACENT / ADJUSTABLE	CT	CERAMIC TILE / COOLING TOWER	FX	FIXTURE	KW	KILOWATTS	PAVT	PAVEMENT	SSTL	STAINLESS STEEL
ACP	ASBESTOS CEMENT PIPE	CTB	CERAMIC TILE BASE	FL	FLOOR	L	LITER	PC	POINT OF CURVATURE / PRIVACY CURTAIN	STA	STATION
ACU	AIR CONDITIONING UNIT	CTF	CERAMIC TILE FLOOR	FM	FORCE MAIN / FACTORY MUTUAL	L	LITER	PCF	POUNDS PER CUBIC FOOT	STD	STANDARD
AD	AREA DRAIN	CTR	CENTER	FP	FIREPROOFING / FIRE PUMP	LA	LABORATORY AIR	PED	PEDESTAL	STE	STANDARD TAPERED END
ADA	AMERICANS WITH DISABILITIES ACT	CTW	CERAMIC TILE WALL	PPM	FEET PER MINUTE	LAB	LABORATORY	PERP	PERPENDICULAR	STIFF	STIFFENER
ADJ	ADJACENT / ADJUSTABLE	CJ	CONDENSING UNIT	FR	FIRE RATED	LAM	LAMINATE	PHC	PREHEAT COIL	STR	STRIP
ADR	ACCESS DOOR	CUH	CABINET UNIT HEATER	FRP	FIBERGLASS REINFORCED PLASTIC	LAV	LAVATORY	PHV	PLUMBING, HEATING, VENTILATING AND AIR CONDITIONING	STL	STEEL
AFF	ABOVE FINISH FLOOR	CUYD	CUBIC YARD	FS	FLOW SWITCH	LBS	POUNDS	PI	POINT OF INTERSECTION	STOR	STORAGE
AHU	AUTHORITY HAVING JURISDICTION	CW	COLD WATER	FT	FEET	LF	LINEAR FEET	PIV	POST INDICATOR VALVE	STR	STRUCTURAL
AHJ	AIR HANDLING UNIT	D	DRAIN / DIFFUSER	FTG	FOOTING	LN	LINEAR	PKG	PARKING	SUSP	SUSPENDED
AL	ALUMINUM	DA	DENTAL AIR	PVC	FIRE VALVE CABINET	LNO	LINOLEUM	PL	PLASTIC LAMINATE / PROPERTY LINE / PLATE	SW	SWITCH
ALT	ALTERNATE	DBL	DOUBLE	G	GAS / GRILLE	LL	LIVE LOAD	PLAS	PLASTER	SWGR	SWITCHGEAR
APC	ACOUSTICAL PANEL CEILING	DEPR	DEPRESSED	G	GAS / GRILLE	LLH	LONG LEG HORIZONTAL	PLAS	PLASTER	SYM	SYMMETRICAL
APPROX	APPROXIMATELY	DEPT	DEPARTMENT	GA	GAGE	LLV	LONG LEG VERTICAL	PLBG	PLUMBING	T	TREAD
AFT	APARTMENT	DET	DETAIL	GALV	GALVANIZED	LMU	LIGHTWEIGHT MASONRY UNITS	PLF	POUNDS PER LINEAR FOOT	TAB	TOP AND BOTTOM
ARCH	ARCHITECT (URAL)	DET	DETAIL	GBD	GRAVITY BACKDRAFT DAMPER	LNG	LONGITUDINAL	PLYWD	PLYWOOD	T&G	TONGUE AND GROOVE
ASPH	ASPHALT	DF	DRINKING FOUNTAIN	GEN	GENERATOR	LPM	LITERS PER MINUTE	PNL	PANEL	TC	TOP OF CURB
ATB	AIR TERMINAL BOX	DIA	DIAMETER	GFRG	GLASS FIBER REINFORCED CONCRETE	LT	LIGHT	POL CONC	POLISHED CONCRETE	TE	TOP ELEVATION
ATC	ACOUSTICAL TILE CEILING	DIAG	DIAGONAL	GI	GALVANIZED IRON	LT WT	LIGHT WEIGHT	PR	PAIR	TEL	TELEPHONE
ATD	AIR TRANSFER DUCT	DIFF	DIFFUSER	GL	GLASS	LV	LABORATORY VACUUM	PRF	POURED RESINOUS FLOORING	TEMP	TEMPERATURE
ATU	AIR TERMINAL UNIT	DIP	DUCTILE IRON PIPE	GLB	GLASS BLOCK	LVL	LEVEL	PROJ	PROJECTION	TERR	TERRAZZO
AUX	AUXILIARY	DISC	DISCONNECT	GLP	GLASS PANEL	LVT	LUXURY VINYL TILE	PRV	PRESSURE REGULATING VALVE	TLT	TOILET
AVG	AVERAGE	DISP	DISTRIBUTION	GLT	GLASS TILE	M	METER	PSI	POUNDS PER SQUARE INCH	TOPO	TOPOGRAPHY
AWT	ACOUSTICAL WALL TREATMENT	DK	DECK	GP	GLAZED PAINT	M	METER	PT	POINT OF TANGENCY	TOS	TOP OF STEEL
AZ	AZIMUTH	DL	DEAD LOAD	GM	GALLONS PER MINUTE	M2	SQUARE METER	PTB	PORCELAIN TILE BASE	TOW	TOP OF WALL
B		DN	DOWN	GR	GRADE	M3	CUBIC METER	PTF	PORCELAIN TILE FLOOR	TP	TOP OF PAVEMENT
BB	BALLED AND BURLAPPED	DO	DITTO	GRV	GRAVITY ROOF VENTILATOR	MA	MAXIMUM	PTVC	POINT OF VERTICAL CURVATURE	TRANS	TRANSVERSE
BD	BOARD	DPR	DAMPER	GWB	GROUT	MAINT	MAINTENANCE	PTW	PORCELAIN TILE WALL	TS	TRANSITION STRIP
BDD	BACK DRAFT DAMPER	DR	DOOR	GT	GYPSPUM WALLBOARD	MB	MARBLE	PVC	POLYVINYL CHLORIDE	TYP	TYPICAL
BDI	BOTTOM ELEVATION	DS	DOWNSPOUT	H	HOLE	MAT	MATERIAL	PVT	POINT OF VERTICAL INTERSECTION	U	UNDERCUT
BL	BUILDING LINE	DV	DENTAL VACUUM	H	HOLE	MAX	MAXIMUM	Q	QUARTZ POLYMER	UC	UNDERGROUND
BLDG	BUILDING	DWG	DRAWING	HB	HOSE BIBB	MB	METAL BASE	QTB	QUARRY TILE BASE	UH	UNIT HEATER
BLKG	BLOCKING	DWL	DOWEL	HC	HEATING COIL	MD	MEDIUM DENSITY OVERLAY	QTF	QUARRY TILE FLOOR	UNO	UNLESS NOTED OTHERWISE
BM	BENCH MARK / BEAM	DWP	DOMESTIC WATER PUMP	HDW	HARDWARE	MECH	MECHANICAL	R	RADIUS / REGISTER	UR	URNAL
BR	BARE FOOT	EA	EACH / EXHAUST AIR	ECT	ENTRY CARPET TILE	MET	METAL	RA	RETURN AIR	V	VOLT
BRG	BEARING	EJ	EACH FACE / EXHAUST FAN	EF	EXPANSION JOINT	MG	MOTOR GENERATOR / MEDICAL GAS	RAF	RAISED ACCESS FLOORING	VAV	VARIABLE AIR VOLUME
BTU	BRITISH THERMAL UNIT	EL	ELEVATION	EH	EXHAUST	EL	ELEVATION	RB	RESILIENT BASE	VC	VERTICAL CURVE
BTUH	BRITISH THERMAL UNIT PER HOUR	ELEC	ELECTRICAL	HP	HORSEPOWER	MIN	MINIMUM	RCP	REINFORCED CONCRETE PIPE	VCP	VITRIFIED CLAY PIPE
C	CENTER TO CENTER	ELEV	ELEVATION	HP	HORSEPOWER	MLO	MAIN LUGS ONLY	RD	ROOF DRAIN	VCT	VINYL COMPOSITION TILE
CAS	CABINET	EMBED	EMBEDMENT	HPT	HIGH POINT	MM	MILLIMETER	REF	REFERENCE	VERT	VERTICAL
CB	CIRCUIT BREAKER / CATCH BASIN	EMD	ESTIMATED MAXIMUM DEMAND	HR	HOUR	MO	MASONRY OPENING	REFL	REFLECTED	VEST	VESTIBULE
CC	COOLING UNIT	EMT	ELECTRICAL METAL TUBING	HS	HIGH STRENGTH	MP	METAL PANEL	REG	REGISTER	VFB	VARIABLE FREQUENCY DRIVE
CE	COVER ELEVATION	ENG	ENTRANCE GRATING	HT	HEIGHT	MT	METAL TRANSITION	REINF	REINFORCED	VTR	VENT THROUGH ROOF
CEM	CEMENT	EP	EPOXY PAINT	HTG	HEATING	MTD	MOUNTED	REQD	REQUIRED	VWC	VINYL WALL COVERING
CFM	CUBIC FEET PER MINUTE	EQ	EQUAL	HTR	HEATER	MTG	MOUNTING	REV	REVERSE / REVISION	W	WATT / WATER
CG	CORNER GUARD	EQUIP	EQUIPMENT	HWC	HEATING, VENTILATING AND AIR CONDITIONING	MULL	MULLION	RF	RETURN FAN	WI	WITH
CH	CHILLER	ET	EXPANSION TANK / EPOXY TERRAZZO	HW	HOT WATER	N	NITROGEN	RGS	RIGID GALVANIZED STEEL	WIO	WITHOUT
CI	CURB INLET / CAST IRON	ETB	EPOXY TERRAZZO INTEGRAL COVE BASE	HWT	HOT WATER CIRCULATING	N	NITROGEN	RH	ROOF HOOD / RELATIVE HUMIDITY / REHEAT	RHC	REHEAT COIL
CIP	CAST IRON PIPE	EVAC	MEDICAL GAS EVACUATION	HZ	HERTZ	N	NITROGEN	RM	ROOM	WC	WATER CLOSET / WALL COVERING
CJ	CONTROL JOINT OR CONTRACTION JOINT	EW	EACH WAY	I	INCH	IA	INSTRUMENT AIR	RO	ROUGH OPENING	WD	WOOD
CKT	CIRCUIT	EWG	ELECTRICAL WATER COOLER	IC	INTERCOM	ICW	ELECTRICAL WATER HEATER	ROW	RIGHT OF WAY	WOB	WOOD BASE
CL	CENTER LINE	EXH	EXHAUST	ID	INSIDE DIAMETER	NC	NOT IN CONTRACT	RS	RESILIENT SHEET	WOF	WOOD FLOOR
CLG	CEILING	EXP	EXPOSED	IE	INVERT ELEVATION	NO	NUMBER	RT	RESILIENT TILE	WOP	WOOD PANEL
CLO	CLOSED	EXPN	EXPANSION	IF	INSIDE FACE	NOM	NOMINAL	S	STAR / STAIN / SURFACE / SANITARY	WDW	WINDOW
CLR	CLEAR	EXT	EXISTING	IN	INCH	NTS	NOT TO SCALE	SA	SUPPLY AIR / SOUND ATTENUATOR	WDF	WOOD FLOOR
CM	CENTIMETER	EXT	EXTERIOR	INSUL	INSULATION	O	OFFSET	SCH	SCHEDULE	WPF	WATERPROOFING
CMH	CUBIC METER PER HOUR	F	FIRE MAIN	J	JOINT	OIS	OFFSET	SD	SUB DRAIN / STORM SEWER	WS	WATER STOP
CMU	CORRUGATED METAL PIPE	FA	FAN ALARM	JAN	JANITOR	OPNG	OPENING	SECT	SECTION	WT	WEIGHT / WINDOW TREATMENT
CMP	CONCRETE MASONRY UNIT	FD	FLOOR DRAIN / FIRE DAMPER	JB	JUNCTION BOX	OPP	OPPOSITE	SHT	SHEET	WWF	WELDED WIRE FABRIC
CO	CLEANOUT / CARBON MONOXIDE	FD / SD	COMBINATION FIRE AND SMOKE DAMPER	JST	JOIST	OX	OXYGEN	SIM	SIMILAR	X	TRANSFORMER
CO2	CARBON DIOXIDE	FDC	FIRE DEPARTMENT CONNECTION	JT	JOINT	Q	QUANTITY	SOG	SUB ON-GRADE	Y	YARD
COL	COLUMN	FDN	FOUNDATION	K	KILO	QZ	OUNCE	SPEC	SPECIFICATIONS	YH	YARD HYDRANT
COMB	COMBINATION / COMBINE	FE	FIRE EXTINGUISHER	KC MIL	THOUSAND CIRCULAR MILS			SQ	SQUARE		
COMP	COMPRESSIBLE	FEC	FIRE EXTINGUISHER CABINET	KIT	KITCHEN						


GENERAL NOTES ARCHITECTURAL

- A. PARTITION AND WALLS
1. DIMENSIONS ARE TO FINISH FACE OF PARTITIONS, FACE OF EXISTING FINISH OR CENTER LINE OF COLUMNS UNLESS SHOWN OR NOTED OTHERWISE. ALL EXISTING DIMENSIONS ARE BASED ON EXISTING DRAWINGS BUT MUST BE VERIFIED IN FIELD.
2. ALL PARTITIONS SHALL EXTEND FROM FLOOR TO UNDER SIDE OF DECK ABOVE EXCEPT WHERE NOTED OR SHOWN OTHERWISE.
3. EXTEND ALL SOUND RATED PARTITIONS TO THE UNDER SIDE OF DECK ABOVE TO PREVENT SOUND TRANSMISSION. FURNISH 4-1/4 POUNDS DENSITY GLASS FIBER INSULATION SHAPED TO FIT THE VOID ABOVE THE PARTITION WHERE AIR-BORNE SOUND CAN PENETRATE SPACES.
4. FOR LOCATIONS OF FIRE-RATED PARTITIONS SEE LS-101 AND LS-102.
5. CONTROL JOINTS SHALL BE PROVIDED ABOVE DOORS AT EACH SIDE IN STUD AND GWB PARTITIONS.
6. EXPANSION JOINTS AT ALL FLOORS, CEILINGS AND WALLS THAT ARE EXPOSED TO VIEW SHALL BE COVERED WITH EXPANSION JOINT COVERS APPROPRIATE FOR FINISHED SURFACES.
7. ALL COLUMNS WITHIN FINISHED SPACES SHALL BE FINISHED WITH SAME MATERIALS SCHEDULED AT WALLS UNLESS OTHERWISE SHOWN OR DETAILED.
8. PROVIDE ALL WALL AND FLOOR OPENINGS FOR MECHANICAL AND ELECTRICAL ITEMS. ALL OPENINGS MORE THAN 16 INCHES WIDE IN MASONRY PARTITIONS SHALL HAVE LINTELS AS SCHEDULED ON THE STRUCTURAL DRAWINGS.
9. PROVIDE CORNER GUARDS AT ALL OUTSIDE CORNERS.
10. PROVIDE MOLD-RESISTANT GWB AT BUILD-OUT, TYPICAL.
11. FOR WALL PARTITION TYPES, SEE SHEET AE-600.
- B. DOORS AND FRAMES
1. PROVIDE LABELS ON DOORS AND FRAMES WHERE SCHEDULED.
2. INSTALL CONTINUOUS CAULKING AROUND METAL FRAMES UNLESS NOTED OTHERWISE.
3. HOLLOW METAL FRAMES SHALL BE ANCHORED TO THE STRUCTURAL FLOOR WITH A MINIMUM OF TWO (2) ANCHOR BOLTS.
4. HOLLOW METAL FRAMES IN STUD PARTITIONS SHALL BE FILLED WITH GROUT TO THE DEPTH OF THE FRAME ANCHOR FULL HEIGHT FOR SOUND DAMPENING BEFORE SETTING IN PLACE.
5. INSTALL CASING BEADS AND CAULK WHERE GWB ABUTS METAL FRAMES.
6. DOOR TYPES AND SIZES ARE SHOWN ON SHEET AE-600.
- C. MISCELLANEOUS
1. SEE PHYSICIST'S REPORT FOR SHIELDING REQUIREMENTS INCLUDING LOCATIONS AND MINIMUM LEAD THICKNESS FOR SURFACES.

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS			CONSULTANT		ARCHITECT/ENGINEER OF RECORD		STAMP		Drawing Title		Phase		Project Title		Project Number	
NO. DESCRIPTION DATE					A/E: RGD CONSULTING ENGINEERS 561-743-0165 / 407-845-6830 WWW.RGDENGINEERS.COM 121 S ORANGE AVE, #120, ORLANDO, FL 32811 CERT OF AUTH 5454		ROBERT G DAVENPORT INGENIERO LICENCIADO L.C. 20229 EXPIRA PUERTO RICO FMS Project and Section VA U.S. Department of Veterans Affairs		SHEET INDEX, GENERAL NOTES, SYMBOLS AND ABBREVIATIONS		CD(100%CD-ISSUE FOR BID)		VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS		672-22-810	
									Approved:				Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		Building Number 1	
											FULLY SPRINKLERED		Issue Date 04/22/2024		Drawing Number GI-002	
													Checked RSM		Drawn PJG	





1 Proposed Debris Plan  
1" = 20'-0"

2 ENLARGED PLAN DURING CONSTRUCTION  
3/16" = 1'-0"

#### CONSTRUCTION BARRIER PLAN NOTES

- THE CONTRACTOR IS TO UTILIZE THE PATH OF TRAVEL INDICATED ON THESE PLANS FOR ACCESSING THE AREAS TO BE RENOVATED. NO OTHER AREA WITHIN THE HOSPITAL IS TO BE ENTERED OR USED BY THE CONTRACTOR WITHOUT THE WRITTEN PERMISSION OF THE HOSPITAL'S AUTHORIZED REPRESENTATIVE.
- THE CONTRACTOR SHALL PROVIDE A CONSTRUCTION ACCESS POINT AS WELL AS THE PROPOSED HOURS OF OPERATION AND CONSTRUCTION STAGING AREAS PRIOR TO THE START OF CONSTRUCTION FOR THE REVIEW AND APPROVAL OF MOUNT SINAI MEDICAL CENTER.
- THE CONTRACTOR IS TO COMPLY WITH THE INFECTION CONTROL REQUIREMENTS AS DEFINED IN THESE DOCUMENTS AND AS PROVIDED IN THE INSTRUCTIONS TO BIDDERS.
- INSTALL TEMPORARY UPRIGHT SPRINKLERS PRIOR TO CEILING REMOVAL TO ALLOW FOR CONTINUED SPRINKLER PROTECTION WITHIN THE CONSTRUCTION AREA.
- DOCUMENT THAT THE FIRE PROTECTION DURING CONSTRUCTION MUST COMPLY WITH VA MASTER CONSTRUCTION SPECIFICATIONS. (NOTE: SPECIFICATION SECTION 01 35 26, SAFETY REQUIREMENTS, ADDRESSES NFPA 241 JOINT COMMISSION INTERIM LIFE SAFETY MEASURES, HOT WORK PERMITS, ETC. (VAFPM SECTION 1.4))

#### INFECTION CONTROL REQUIREMENTS

THIS PROJECT HAS BEEN DETERMINED TO REQUIRE TYPE IV CLASS IV HIGHEST RISK GROUP PRECAUTIONS TO PROTECT THE INHABITANTS OF THE FACILITY DURING THE CONSTRUCTION PROCESS. THE GENERAL CONTRACTORS AND SUBCONTRACTORS AND STAFF WILL BE REQUIRED TO COMPLY WITH THE HOSPITAL'S CRITERIA AND PROCEDURES FOR INFECTION CONTROL AND CONTAINMENT OF CONTAMINANTS DURING THE CONSTRUCTION PROCESS. THE CONTRACTOR WILL BE PROVIDED WITH THESE REQUIREMENTS AS PART OF THE CONTRACT DOCUMENTS AND WILL BE REQUIRED TO PROVIDE ALL NECESSARY MATERIALS, EQUIPMENT AND LABOR AS PART OF HIS BID TO INSURE THE REQUIREMENTS ARE ACHIEVED. THE CONTRACTOR WILL BE REQUIRED TO UTILIZE THE METHOD OF ACCESS AND EGRESS AS INDICATED ON THE CONSTRUCTION ACCESS PLANS. ALL CONSTRUCTION MATERIALS ARE TO BE ENCLOSED OR CONTAINED WHILE BEING TRANSPORTED WITHIN THE HOSPITAL. THE CONTRACTOR WILL BE REQUIRED TO THOROUGHLY CLEAN AND POLICE ALL AREAS UTILIZED BY THE CONTRACTOR FOR DELIVERIES, STAGING, STORAGE, TRANSPORTING AND CONSTRUCTION. NO EXTERIOR OR INTERIOR AREAS SHALL BE LEFT WITH UNSUPERVISED CONSTRUCTION MATERIALS OR DEBRIS. THE CONTRACTOR WILL BE REQUIRED TO PROTECT AND CLEAN ALL EXTERIOR AND INTERIOR AREAS UTILIZED FOR THE CONSTRUCTION PROCESS IMMEDIATELY AFTER USE.


#### GENERAL NOTES

- ALL AREAS OF CONSTRUCTION SHALL MAINTAIN NEGATIVE AIR PRESSURE RELATIVE TO ADJACENT SPACES FOR THE DURATION OF CONSTRUCTION ACTIVITIES. REFER TO THE MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION.
- IF CONTRACTOR SHOULD NEED TO ACCESS MECHANICAL, ELECTRICAL, PLUMBING, ETC., FROM ANY FLOOR ABOVE OR BELOW, THE CONTRACTOR MUST TAKE ACTION TO RESTORE ALL INFRASTRUCTURE AND FINISH TO ORIGINAL PRE-CONSTRUCTION CONDITION.
- CONTRACTOR SHALL COORDINATE ANY AND ALL SHUTDOWNS WITH THE OWNER AS PER THE OWNER PROVIDED PRE-CONSTRUCTION RISK ASSESSMENT REPORTS.
- CONTRACTOR SHALL COORDINATE ANY DISRUPTIONS WITH OWNER AS PER THE OWNER PROVIDED PRE-CONSTRUCTION RISK ASSESSMENT REPORTS. IF THERE ARE ANY CONFLICTS, CONTRACTOR SHALL CONTACT THE OWNER/ARCHITECT IMMEDIATELY AS TO NOT HOLD UP PROJECT COMPLETION.
- CONTRACTOR SHALL AT ALL TIMES MAINTAIN CLEAR AND UNOBSTRUCTED ACCESS TO CORRIDORS AND STAIRS FOR EMERGENCY EGRESS.
- CONTRACTOR SHALL VERIFY FIELD CONDITIONS PRIOR TO BIDDING AND CONSTRUCTION TO FAMILIARIZE THEMSELVES WITH EXISTING CONDITIONS AND SCOPE OF WORK REQUIRED.
- ALL WATER LINES IMPACTED BY DEMOLITION SHALL BE CAPPED WHEN NOT IN USE. WATER LINES SHALL BE FLUSHED AFTER FINAL INSTALLATION. REFER TO SPECIFICATIONS FOR FLUSHING REQUIREMENTS.

#### LEGEND

- CONTRACTOR ROUTE TO CONSTRUCTION AREA
- TEMPORARY CONSTRUCTION BARRIER CONSISTING OF METAL STUD FRAMING WITH 58" TYPE 'X' GWS ON ONE SIDE, TAPED WITH CAULKED SEAMS CREATING A TIGHT SEAL ON ALL SIDES
- TEMPORARY CONSTRUCTION ANTE ROOM AS MANUFACTURED BY KONTROL, KUBE OR MINTIE AND COMPLYING WITH NFPA 701
- PROJECT SCOPE
- (-) NEGATIVE PRESSURE DIFFERENTIAL COMPARED TO SURROUNDING ROOMS
- (+) POSITIVE PRESSURE DIFFERENTIAL COMPARED TO SCANNING ROOM AND CONTROL ROOM

#### PROJECT LOCATION



CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS		
NO.	DESCRIPTION	DATE

CONSULTANT

ARCHITECT/ENGINEER OF RECORD

A/E:  
**RGD**  
CONSULTING  
ENGINEERS  
JUPITER, FLORIDA  
561-743-0165 | 407-845-6830  
WWW.RGDENGINEERS.COM  
121 S ORANGE AVE #120, ORLANDO, FL 32811  
CERT OF AUTH 5454

STAMP



FMS  
Project and  
Section

VA U.S. Department of  
Veterans Affairs

Drawing Title  
PROPOSED DEBRIS REMOVAL

Approved:

Phase  
CD(100%CD-ISSUE FOR BID)

FULLY SPRINKLERED


Project Title  
VA PROVIDE HIGH LEVEL  
DISINFECTION FOR SPS

Location 10 CALLE CASIA - ADM. BLDG. SUITE  
4M456 SAN JUAN, PR 00921-3201


Issue Date 04/22/2024  
Checked RSM  
Drawn PJG

Project Number  
672-22-810  
Building Number  
1

Drawing Number  
LS-002



1 Demolition Phase 1 1/2" = 1'-0"			2 Demolition Phase 2 1/2" = 1'-0"		
REVISIONS			CONSULTANT		
NO.	DESCRIPTION	DATE	ARCHITECT/ENGINEER OF RECORD		
			A/E: RGD CONSULTING ENGINEERS		
			JUPITER   ORLANDO 561-743-0165   407-945-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #120, ORLANDO, FL 32811 CERT OF AUTH 5454		
			STAMP		
			ROBERT G DAVENPORT INGENIERO LICENCIADO LIC. 24629 EXPIRA PUERTO RICO		
			FMS Project and Section VA U.S. Department of Veterans Affairs		
			Drawing Title DEMO PLAN		
			Approved:		
			Phase CD(100%CD-ISSUE FOR BID)		
			Project Title VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS		
			Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		
			Issue Date 04/22/2024		
			Checked RSM		
			Drawn P/JG		
			Project Number 672-22-810		
			Building Number 1		
			Drawing Number AE-101A		




CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS		
NO.	DESCRIPTION	DATE

CONSULTANT

ARCHITECT/ENGINEER OF RECORD
A/E: <b>RGD CONSULTING ENGINEERS</b> JUPITER   ORLANDO 561-743-0165   407-845-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE. #120, ORLANDO, FL 32811 CERT OF AUTH 5454

STAMP



<b>FMS Project and Section</b> <b>VA</b> U.S. Department of Veterans Affairs
---

Drawing Title <b>PROPOSED FLOOR PLAN</b>
Approved:


Phase CD(100%CD-ISSUE FOR BID)
<b>FULLY SPRINKLERED</b>

Project Title <b>VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS</b>
Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201
Issue Date 04/22/2024
Checked RSM
Drawn P/JG

Project Number <b>672-22-810</b>
Building Number <b>1</b>
Drawing Number <b>AE-101B</b>









# 1 CEILING DEMO PLAN




2 PROPOSED REFELCTED CEILING PLAN  
1/2" = 1'-0"

## LEGEND

	DEMOLISHED CEILING
	NEW CEILING
	2'X4' LED LIGHT FIXTURE
	2'X2' SUPPLY REGISTER
	2'X2' RETURN REGISTER



CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD	STAMP	FMS Project and Section	VA U.S. Department of Veterans Affairs	Drawing Title REFLECTED CEILING PLAN	Phase CD(100%CD-ISSUE FOR BID)	Project Title VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS	Project Number 672-22-810	
NO.	DESCRIPTION	DATE		A/E: <div><div>RGD CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-763-3115   407-845-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE. #1200, ORLANDO, FL 32811 CERT OF AUTH 5454</div></div>	<div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div></div><div>LIC. 24629 EXPIRA</div><div>PUERTO RICO</div></div>			Approved:		Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201	Drawing Number AE-122A	
									FULLY SPRINKLERED	Issue Date 04/22/2024	Checked RSM	Drawn PJG

A


B

C


D

E


F




1 STERILE SIDE  
1/2" = 1'-0"




2 ELEVATION DECONTAMINATION SIDE  
1/2" = 1'-0"




3 AER MACHINE WALL SECTION  
3/4" = 1'-0"




4 ELEVATION STERILE SIDE  
1/2" = 1'-0"



5 ELEVATION WALL OUTSIDE DECONTAMINATION  
1/2" = 1'-0"



6 HM FRAME DOOR DETAILS  
3\"/>



7 HM FRAME DOOR DETAILS  
3\"/>

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS		
NO.	DESCRIPTION	DATE

CONSULTANT

ARCHITECT/ENGINEER OF RECORD
A/E: <b>RGD</b> CONSULTING ENGINEERS JUPITER   ORLANDO 561-743-0165   407-945-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE, #120, ORLANDO, FL 32811 CERT OF AUTH 5454

STAMP

FMS Project and Section
U.S. Department of Veterans Affairs


Drawing Title
INTERIOR ELEVATIONS AND DETAILS
Approved:

Phase
CD(100%CD-ISSUE FOR BID)
FULLY SPRINKLERED

Project Title
VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS
Location
10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201
Issue Date
04/22/2024
Checked
RSM
Drawn
PJG

Project Number
672-22-810
Building Number
1
Drawing Number
AE-405

A



PARTITION TYPES LEGEND

ROOM FINISH SCHEDULE									
ROOM #	ROOM NAME	FLOOR	BASE	WALLS				CEILING	
				NORTH	SOUTH	EAST	WEST		
101	SCOPE HLD PROCESSING AREA	EPOXY RESIN SAND RESIN AND PREP TOP COAT FOR SMOOTH FINISH (TYP.)	6\"/>	EPOXY PAINT	EPOXY PAINT	EPOXY PAINT	EPOXY PAINT	EPOXY PAINT	

Room Finish Schedule

GENERAL NOTES:

1. PROVIDE MINIMUM 0.0312\"/>
2. PROVIDE MINIMUM 0.0312\"/>
3. USE 5/8\"/>
4. SEE ALL SPECIFICATIONS FOR GWB REQUIREMENTS @ TOILETS AND ALL WET AREAS.
5. APPLIES TO POWER AND COMMUNICATIONS, ETC.
  - A) BACK-TO-BACK PLACEMENT OF OUTLET BOXES NOT PERMITTED.
  - B) PLUG ALL UNUSED KNOCK-OUTS IN OUTLET BOXES WITH KNOCK-OUT CAPS.
  - C) PROVIDE 1/4\"/>
  - D) DEPTH OF OUTLET BOX TO BE COMPATIBLE WITH STUD SIZES IN ORDER TO ACCOMMODATE BOX PAD.
6. PROVIDE BLOCKING @ WALL HUNG CASEWORK, EQUIPMENT, SHELVES, COUNTERTOPS, HEAVY WALL SCONCES, AND MAJOR ARTWORK.

INTERIOR STUD CHART NOTES:

\* REFERENCE STEEL STUD MANUFACTURER ASSOCIATION'S STANDARDS FOR SECTION PROPERTIES AND DESIGN OF STUD SIZE LISTED HERE.

USE L240 DEFLECTION CHART FOR ALL AREAS UNLESS OTHERWISE NOTED.

GEN NOTES & SPACING CHART

INTERIOR STUD GAGE AND SPACING CHART*						
STUD WIDTH	DESIGN THICKNESS (GAGE)	STUD SPACING (INCHES)	PARTITION HEIGHT			BRACING SPACING WHERE OCCURS
			DEFLECTION VALUE 5 psf			
			L/120	L/240	L/360	
1 5/8"	0.0179" (25)	16"	10'-7"	8'-4"	-	4'-0" OC
	0.0312" (20)	24"	9'-9"	7'-11"	-	4'-0" OC
	0.0312" (20)	16"	12'-1"	9'-8"	8'-5"	4'-0" OC
2 1/2"	0.0179" (25)	16"	13'-3"	11'-3"	9'-10"	6'-0" OC
	0.0312" (20)	24"	11'-10"	10'-7"	9'-3"	6'-0" OC
	0.0312" (20)	16"	16'-5"	12'-10"	11'-2"	6'-0" OC
3 5/8"	0.0179" (25)	24"	14'-10"	11'-7"	10'-0"	6'-0" OC
	0.0179" (25)	16"	15'-4"	14'-4"	12'-4"	8'-0" OC
	0.0312" (20)	24"	13'-9"	13'-5"	11'-7"	8'-0" OC
4"	0.0179" (25)	16"	20'-8"	16'-5"	14'-3"	8'-0" OC
	0.0179" (25)	24"	18'-6"	14'-9"	12'-9"	8'-0" OC
	0.0312" (20)	16"	17'-2"	15'-4"	13'-4"	8'-0" OC
6"	0.0312" (20)	24"	15'-1"	14'-2"	12'-4"	8'-0" OC
	0.0312" (20)	16"	23'-1"	18'-4"	15'-11"	8'-0" OC
	0.0179" (25)	24"	20'-9"	16'-5"	14'-3"	8'-0" OC
6"	0.0179" (25)	16"	19'-9"	19'-9"	17'-11"	10'-0" OC
	0.0179" (25)	24"	16'-9"	16'-9"	16'-9"	10'-0" OC
	0.0312" (20)	16"	30'-10"	24'-6"	21'-4"	10'-0" OC
6"	0.0312" (20)	24"	27'-2"	21'-7"	18'-10"	10'-0" OC

HARDWARE SCHEDULE AND NOTES

SET NO.1  
DOORS: B & C

- 3 - HINGES - 41/2"X41/2" - BB1279 NRP  
1 - STOREROOM LOCK - D80PD  
2 - CLOSER - 4041  
2 - SILENCERS - SR64  
1 - WEATHER STRIPING - 160SDKB - 1-102A, 1-103A, R-100A ONLY

SET NO.2  
DOOR: A

- 3 - HINGES - 41/2"X41/2" - BB1279 NRP  
1 - CLOSER - 4041  
3 - SILENCERS - SR64  
1 - FLOOR STOP - 441  
1 - PRIVACY SET - D405

Hardware Schedules & Notes


DOOR AND FRAME SCHEDULE - NOTES

1. THE CONTRACTOR SHALL CAREFULLY STUDY AND COMPARE THE CONTRACT DOCUMENTS AND THIS SCHEDULE AND SHALL REPORT IN WRITING TO THE ARCHITECT ANY ERROR, INCONSISTANCY OR OMISSION THAT HE MAY DISCOVER.
2. ALL FRAMES SHALL BE CAULKED CONTINUOUSLY TO THE WALL ON BOTH SIDES.
3. DOOR SHALL BE ARRANGED TO BE OPENED READILY FROM THE EGRESS SIDE WHENEVER THE BUILDING IS OCCUPIED. LOCKS, IF PROVIDED SHALL NOT REQUIRE THE USE OF A KEY, TOOL, SPECIAL KNOWLEDGE, OR EFFORT FOR OPERATION FROM THE INSIDE OF THE BUILDING AS PER NFPA 101 5-2.1.5.
4. ALL HOLLOW METAL FRAMES SHALL BE WELDED CONSTRUCTION, "KNOCK-DOWN" TYPE HOLLOW METAL FRAMES WILL NOT BE ALLOWED.
5. ALL TOP OF HOLLOW METAL FRAMES (DOORS & GLASS OPENINGS) TO ALIGN, FOR ADDITIONAL HORIZONTAL MULLIONS TO GLASS OPENING FRAMES REFER TO INTERIOR ELEVATIONS AS NOTED ON THE DRAWINGS.
6. ALL EXTERIOR DOORS SHALL BE FULLY WEATHERSTRIPPED.
7. ALL DOOR AND FRAME TO BE PAINTED (SEE SPECS.)
8. VERIFY WITH OWNER HARDWARE STANDARDS, MATCH ALL OWNER STANDARDS.
9. ALL DOORS SHALL HAVE STOPS, (GYNN-JOHNSON 50C WALL &/OR FB-13 FLOOR)
10. ALL LATCHES SHALL BE LEVER.
11. ALL HARDWARE SHALL HAVE 626 SATIN CHROMIUM FINISH OR FINISH AS SELECTED BY OWNER.
12. ALL DOORS EXISTING AND NEW KEYPED DOORS SHALL RECEIVE NEW LOCK CORES AND SHALL BE KEYPED TO MASTER. PROVIDE OWNER WITH 10 MASTER KEYS.
13. PROVIDE AND INSTALL BRUSHED S.S. KICK PLATES ON ALL PUSH SIDES OF DOORS 10" HIGH 2" L.D.W.
14. DOORS TO BE LOCKED BY ELECTRIFIED PANIC HARDWARE DEVICE TO PROVIDE POSITIVE LATCHING ON FIRE RATED DOOR. LOCATE CARD READER ON STRIKE SIDE AND CONNECT TO ELECTRIC PANIC TO PROVIDE ENTRY. EGRESS WILL BE BY PANIC FUNCTION AT ALL TIMES.

PRODUCT	SPECIFIED MANUFACTURER
1. HINGES	HAGER
2. LOCKS & LATCHES	SCHLAGE
3. CYLINDERS, KEYS, KEYING	SCHLAGE
4. EXIT DEVICES	VON DUREN
5. DOOR CLOSERS	LCN
6. AUTO OPERATORS	STANLEY
7. DH STOPHOLDERS	CLYNN-JOHNSON
8. MAGNETIC HOLD OPENS	LCN
9. WALL STOPS/FLOOR STOPS, FLUSHBOLTS	ROCKWOOD
10. KICK PLATES	ROCKWOOD
11. THRESHOLD/WEATHER-STRIP	NATIONAL GUARD
12. SILENCERS	IVES
13. COORDINATORS	ROCKWOOD
14. ASTRAGALS	PEMCO

Door and Frame Schedule - Notes

HM FRAME DOOR DETAILS




PARTITION TYPES

GENERAL NOTES:


1. G.C. SHALL COORDINATE WITH METAL FRAMING FABRICATOR. FABRICATOR WILL PROVIDE SHOP DRAWING FOR ALL LIGHT GAUGE FRAMING CONSTRUCTION (TYP.)

DOOR TYPES



Door Types

DOOR FRAME TYPES




Door Frame Types

DOOR AND FRAME SCHEDULE


DOOR MARK	DOOR SIZE						FRAME				FIRE RATING LABEL	HARDWARE SET NO.	KEYSPACE	REMARKS
	WIDTH	HEIGHT	THICK	MAT	TYPE	GLASS	MAT	TYPE	JAMB	HEAD	SILL			
102	3'-0"	7'-0"	1-3/4"	HM	F	-	-	HM	S	CS	CS	-	1	EXT CARD READER - COORD W/ SECURITY & FACILITY

Door & Frame Schedule

SEISMIC SUSPENSION SYSTEM DETAIL



SEISMIC SUSPENSION SYSTEM DETAIL





SEISMIC GYP BD CLG DETAIL

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS		
NO.	DESCRIPTION	DATE

CONSULTANT

ARCHITECT/ENGINEER OF RECORD
A/E: RGD CONSULTING ENGINEERS JUPITER   ORLANDO 561-743-0165   407-945-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE, #120, ORLANDO, FL 32811 CERT OF AUTH 5454



Drawing Title PARTITION TYPES, DOOR SCHEDULE AND DETAILS
Approved:

Phase CD(100%CD-ISSUE FOR BID)
FULLY SPRINKLERED

Project Title VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS
Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201
Issue Date 04/22/2024
Checked RSM
Drawn P/JG

Project Number 672-22-810
Building Number 1
Drawing Number AE-600

A

B

C

D

E

F

A

B

C

D

E

F

MECHANICAL SYMBOLS AND ABBREVIATIONS		
ABBR	SYMBOL	REMARKS
SV		STEAM VENT
CPD		CONDENSATE PUMP DISCHARGE
LPS		LOW PRESSURE STEAM SUPPLY
LPR		LOW PRESSURE STEAM RETURN
MPS		MEDIUM PRESSURE STEAM SUPPLY
MPR		MEDIUM PRESSURE STEAM RETURN
HPS		HIGH PRESSURE STEAM SUPPLY
HPR		HIGH PRESSURE STEAM RETURN
HWS		HEATING HOT WATER SUPPLY
HWR		HEATING HOT WATER RETURN
CHWS		CHILLED WATER SUPPLY
CHWR		CHILLED WATER RETURN
HWS		HOT WATER SUPPLY
HWR		HOT WATER RETURN
CD		CONDENSATE DRAIN
RV		RELIEF VENT
		ISOLATION VALVE
		BUTTERFLY VALVE
		GLOBE VALVE
		PLUG VALVE
		CHECK VALVE
		GAS COCK
		"TACO" BALANCING VALVE
		BALANCING VALVE
PRV		PRESSURE REDUCING VALVE
VB		VACUUM BREAKER
		FLOW MEASURING DEVICE
		PIPE UNION OR FLANGE
		STRAINER
		RELIEF VALVE
		THERMOMETER
		PRESSURE GAGE WITH GAGE COCK
		ARROW INDICATES DOWNWARD PITCH OF PIPE
		ARROW INDICATES DIRECTION OF FLOW
		PIPE ECCENTRIC REDUCER
		PIPE CONCENTRIC REDUCER
		CAPPED END
		PIPE ELBOW UP
		PIPE ELBOW DOWN
		PIPE TEE UP
		PIPE TEE DOWN
		FLEXIBLE CONNECTOR
		EXPANSION JOINT
		AUTOMATIC FLOW CONTROL VALVE
		THERMOSTATIC EXPANSION VALVE
		AUTOMATIC AIR VENT
		MANUAL AIR VENT
		AUTOMATIC TWO-WAY VALVE
		AUTOMATIC THREE-WAY VALVE
		STEAM TRAP
		PIPE ALIGNMENT GUIDE
		PIPE ANCHOR
CO		CLEAN-OUT

MECHANICAL SYMBOLS AND ABBREVIATIONS		
ABBR	SYMBOL	REMARKS
		HORIZONTALLY MOUNTED EXHAUST/RETURN AIR REGISTER/GRILLE
		VERTICALLY MOUNTED EXHAUST/RETURN AIR REGISTER/GRILLE
		HORIZONTALLY MOUNTED SUPPLY AIR ROUND DIFFUSER
		HORIZONTALLY MOUNTED SUPPLY AIR DIFFUSER/REGISTER/GRILLE
		VERTICALLY MOUNTED SUPPLY AIR DIFFUSER/REGISTER/GRILLE
		RECTANGULAR DUCTWORK SUPPLY/OUTSIDE AIR ELBOW UP
		RECTANGULAR DUCTWORK SUPPLY/OUTSIDE AIR ELBOW DOWN
		RECTANGULAR DUCTWORK EXHAUST/RETURN/RELIEF AIR ELBOW UP
		RECTANGULAR DUCTWORK EXHAUST/RETURN/RELIEF AIR ELBOW DOWN
		ROUND DUCTWORK ELBOW UP
		ROUND DUCTWORK ELBOW DOWN
		FLAT-OVAL DUCTWORK ELBOW UP
		FLAT-OVAL DUCTWORK ELBOW DOWN
FD		FIRE DAMPER
FSD		COMBINATION FIRE/SMOKE DAMPER
SD		SMOKE DAMPER
VD		VOLUME DAMPER
AD		AUTOMATIC (MOTORIZED) DAMPER
DSD		DUCT MOUNTED SMOKE DETECTOR
SA		SUPPLY AIR ( " DUCT SIZE )
RA		RETURN AIR ( " DUCT SIZE )
EA		EXHAUST AIR ( " DUCT SIZE )
OA		OUTSIDE AIR ( " DUCT SIZE )
REL A		RELIEF AIR ( " DUCT SIZE )
		FLAT-OVAL DUCT SIZE, FIRST NUMBER INDICATES SIZE FOR SIDE SHOWN
		ROUND DUCT SIZE
		RECTANGULAR DUCT SIZE, FIRST NUMBER INDICATES SIZE FOR SIDE SHOWN
		DETAIL OR SECTION DESIGNATION ( " DETAIL OR SECTION REFERENCE ) ( " SHEET NUMBER DETAIL OR SECTION DRAWN ON )
		NEW TO EXISTING DESIGNATION
		EQUIPMENT DESIGNATION ( " EQUIPMENT MARK NUMBER )
		REFERENCE DESIGNATION ( " NOTE NUMBER )
		REFERENCE DESIGNATION ( " RISER NUMBER )
		HUMIDISTAT OR HUMIDITY SENSOR
		THERMOSTAT OR TEMPERATURE SENSOR
		PRESSURE SWITCH OR PRESSURE SENSOR
		AIR TERMINAL UNIT (W/ HOT WATER REHEAT COIL)
		VENTURI AIR VALVE
		DIFFERENTIAL PRESSURE SENSOR
		CARBON DIOXIDE SENSOR
		NEW TO EXISTING

MECHANICAL ABBREVIATIONS			
ABBR	REMARKS	ABBR	REMARKS
ADJ	ADJUSTABLE	PSIG	POUND(S) PER SQUARE INCH GAGE
ADJ	ADJUSTABLE FREQUENCY DRIVE	QTY	QUANTITY
AF	ABOVE FINISHED FLOOR	REQD	REQUIRED
ALT	ALTERNATE	RH	RELATIVE HUMIDITY
AP	ACCESS PANEL	RL	REFRIGERANT LIQUID
APD	AIR PRESSURE DROP	RPM	REVOLUTIONS PER MINUTE
AVG	AVERAGE	RM	ROOM
BAS	BUILDING AUTOMATION SYSTEM	RS	REFRIGERANT SUCTION
BDD	GRAVITY BACKDRAFT DAMPER	SAT	SATURATION
BTUH	BRITISH THERMAL UNITS PER HOUR	SCFM	STANDARD CFM
CAP	CAPACITY	SHT	SHEET
CFH	CUBIC FEET PER HOUR	SIM	SIMILAR
CFM	CUBIC FEET PER MINUTE	SP	SLUMP PUMP, STATIC PRESSURE
CI	CAST IRON	SQ	SQUARE
CLG	CEILING, COOLING	TD	TEMPERATURE DIFFERENTIAL
COND	CONDENSER, CONDENSATE	TEMP	TEMPERATURE
CONN	CONNECTION	TSP	TOTAL STATIC PRESSURE
DB	DRY BULB	UNO	UNLESS NOTED OTHERWISE
dB	DECIBEL(S)	V	VOLT(S)
DDC	DIRECT DIGITAL CONTROL	VAV	VARIABLE AIR VOLUME
DIA	DIAMETER	VEL	VELOCITY
DN	DOWN	VFD	VARIABLE FREQUENCY DRIVE
DX	DIRECT EXPANSION	VTR	VENT THRU ROOF
EAT	ENTERING AIR TEMPERATURE	W	WATT (S)
EFF	EFFICIENCY	WB	WET BULB
EMCS	ENERGY MANAGEMENT CONTROL SYSTEM	WG	WATER GAUGE
ESP	EXTERNAL STATIC PRESSURE	WPD	WATER PRESSURE DROP
EWT	ENTERING WATER TEMPERATURE		
EXH	EXHAUST		
EXST	EXISTING		
F	FAHRENHEIT		
FL	FLOOR		
FLA	FULL LOAD AMPS		
FLEX	FLEXIBLE		
FPM	FEET PER MINUTE		
FUT	FUTURE		
FXTR	FIXTURE		
GAL	GALLON(S)		
GPH	GALLON(S) PER HOUR		
GPM	GALLON(S) PER MINUTE		
HG	HOT GAS		
HP	HORSEPOWER		
HPS	HIGH PRESSURE STEAM		
HR	HOUR		
HTG	HEATING HOT		
HVAC	HEATING VENTILATING AND AIR CONDITIONING		
HZ	HERTZ		
ID	INSIDE DIAMETER		
IE	INVERT ELEVATION		
IN	INCH (ES)		
I/O	INPUT/OUTPUT		
KW	KILOWATT(S)		
LAT	LEAVING AIR TEMPERATURE		
#	POUNDS		
LBS	POUNDS		
LF	LINEAR FOOT, LINEAR FEET		
LPS	LOW PRESSURE STEAM		
LWT	LEAVING WATER TEMPERATURE		
MAX	MAXIMUM		
MBH	THOUSANDS BTU/HR		
MCC	MOTOR CONTROL CENTER		
MFR	MANUFACTURER		
MISC	MISCELLANEOUS		
MIN	MINUTE(S), MINIMUM		
MPC	MEDIUM PRESSURE CONDENSATE		
MPS	MEDIUM PRESSURE STEM		
MTD	MOUNTED		
NC	NORMALLY CLOSED, NOISE CRITERIA		
NO	NORMALLY OPEN, NUMBER		
NR	NOISE REDUCTION		
NRC	NOISE REDUCTION COEFFICIENT		
NTS	NOT TO SCALE		
OD	OUTSIDE DIAMETER		
O S & Y	OUTSIDE SCREW AND YOKE VALVE		
PC	PUMPED CONDENSATE		
PD	PRESSURE DROP		
PH	PHASE		
PLBG	PLUMBING		
PSI	POUND(S) PER SQUARE INCH		
PSIA	POUND(S) PER SQUARE INCH ABSOLUTE		

### MECHANICAL DEMOLITION NOTES:

- UNLESS OTHERWISE NOTED, ALL MECHANICAL EQUIPMENT AND DEVICES ON WALLS AND CEILING NOT BEING DEMOLISHED ARE EXISTING TO REMAIN UNLESS REQUIRED BY NEW CONSTRUCTION. COORDINATE WITH VA RESIDENT ENGINEER ANY ADDITIONAL ITEMS WHICH WILL BE SALVAGED OR ARE TO REMAIN.
- DEMOLITION WORK IS SHOWN IN DASHED LINES AND HEAVY PENWEIGHT. EXISTING WORK TO REMAIN IS SHOWN IN SOLID LINE AND LIGHT PENWEIGHT.
- PROVIDE ALL MECHANICAL DEMOLITION WORK NECESSARY TO INSTALL NEW WORK. CONTRACTOR SHALL REROUTE AND RECONNECT ANY SYSTEMS THAT WILL REMAIN IN USE BUT INTERFERES WITH NEW CONSTRUCTION.
- EXISTING MECHANICAL ITEMS THAT ARE BEING REMOVED AND NOT TO BE REUSED IN THE NEW CONSTRUCTION SHALL BE DISPOSED OF AS DIRECTED. REMOVAL AND DISPOSAL OF THE EXISTING ITEMS IS THE CONTRACTORS RESPONSIBILITY.
- IF THE CONTINUITY OF MECHANICAL DEVICES AND EQUIPMENT REMOVED IN THE AREAS OUTSIDE THIS DEMOLITION WORK AREA IS INTERRUPTED, THE CONTRACTOR SHALL INSTALL REQUIRED DUCTWORK/PIPING TO INSURE THE CONTINUITY OF SYSTEMS TO EXISTING AREAS OUTSIDE THE DEMOLITION AREAS. DRAWINGS ARE BASED ON EXISTING PLANS AND FIELD INVESTIGATION WITHOUT DEMOLITION. CONTRACTOR SHALL VISIT EXISTING BUILDING AND FAMILIARIZE HIM/HER-SELF WITH EXISTING CONDITIONS AND SHALL EXAMINE ALL RELATED DRAWINGS TO AVOID CONFLICTS. ORIGINAL BUILDING DRAWINGS ARE AVAILABLE.
- CONTRACTOR TO COORDINATE WITH ARCHITECTURE, ELECTRICAL, PLUMBING AND OTHER TRADES FOR ALL EQUIPMENT BEING REMOVED. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE ALL MECHANICAL WORK WITH ALL SUBCONTRACTORS, PRIME CONTRACTOR AND OTHERS WHO MAY BE PERFORMING DEMOLITION WORK ADJACENT TO OR INTEGRAL TO THE MECHANICAL WORK.
- ALL EXISTING ITEMS THAT ARE TO BE REINSTALLED SHALL BE INSPECTED AND VERIFIED FOR PROPER OPERATION. IF ANY ITEM IS NOT IN A WORKING CONDITION OR IS DAMAGED, THE ITEM SHALL BE BROUGHT TO THE ATTENTION OF THE VA RESIDENT ENGINEER FOR DIRECTION.
- CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CORING, CUTTING, PATCHING, REPAIRING, REMOVAL, REPLACEMENT, DISCONNECTING, RELOCATIONS, RECONNECTIONS OF EQUIPMENT AS REQUIRED TO ACCOMMODATE THE INSTALLATION OF NEW WORK OR REMOVAL.
- SCHEDULE WORK IN EXISTING BUILDING AT TIMES CONVENIENT TO VA RESIDENT ENGINEER.
- INFORM VA RESIDENT ENGINEER IN ADVANCE OF ANY SHUT DOWN THAT WILL OCCUR AND GIVE ESTIMATE OF DURATION. BEGIN WORK ONLY AFTER CONTRACTING OFFICER HAS AGREED TO SHUT DOWN.
- THOROUGHLY INSPECT MECHANICAL SYSTEMS IN REWORKING AREAS AND BRING TO THE ATTENTION OF THE CONTRACTING OFFICER ALL DEFECTIVE OR UNSERVICABLE MATERIAL, NOT SCHEDULED FOR REMOVAL OR REPLACEMENT.
- BEFORE REMOVAL OF EQUIPMENT TO BE RELOCATED, VERIFY PROPER OPERATION WITH THE VA RESIDENT ENGINEER.
- NOTIFY VA RESIDENT ENGINEER OF ANY EQUIPMENT DAMAGED OR NOT OPERATING PROPERLY. THE CONTRACTOR IS RESPONSIBLE FOR PROPER OPERATION AND CONDITION OF EQUIPMENT AFTER REMOVAL. ANY EQUIPMENT DAMAGE DUE TO IMPROPER INSTALLATION SHALL BE REPLACED BY THE CONTRACTOR.
- REMOVE AND RELOCATE ALL MECHANICAL WORK AS REQUIRED TO PROVIDE WORK OF OTHER TRADES. PROVIDE ALL MECHANICAL MATERIALS AND LABOR NECESSARY TO RELOCATE MECHANICAL WORK.
- ITEMS INDICATED TO BE RETURNED TO THE VA RESIDENT ENGINEER SHALL BE DELIVERED TO THE LOCATION ON SITE DESIGNATED BY THE VA RESIDENT ENGINEER.

### MECHANICAL GENERAL NOTES:


- ALL WORK SHALL CONFORM TO FEDERAL, STATE AND LOCAL LAWS, CODES AND ORDINANCES.
- THE MECHANICAL DRAWINGS ARE DIAGRAMMATIC ONLY.
- THE CONTRACTOR IS REQUIRED TO FURNISH ALL LABOR, MATERIAL AND EQUIPMENT TO COMPLETE THE PROJECT. PROVIDE IN THE SAME OR AS CLOSE TO THE SAME LOCATION ALL MECHANICAL DEVICES AND EQUIPMENT REMOVED IN THE DEMOLITION PHASE. WORK SHALL BE PERFORMED BY SKILLED WORKERS IN THEIR RESPECTIVE TRADES FOLLOWING MANUFACTURERS RECOMMENDATIONS.
- EXISTING WORK TO REMAIN IS SHOWN IN SOLID LINES AND LIGHT PENWEIGHT. NEW WORK IS SHOWN IN HEAVY PENWEIGHT.
- CONTRACTOR TO COORDINATE ARCHITECTURAL, ELECTRICAL, PLUMBING AND OTHER TRADES FOR ALL EQUIPMENT BEING INSTALLED. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE ALL MECHANICAL WORK WITH ALL SUBCONTRACTORS, PRIME CONTRACTOR AND OTHERS WHO MAY BE PERFORMING INSTALLATION WORK ADJACENT TO OR INTEGRAL TO THE MECHANICAL WORK.
- WORK REQUIRING SHUT DOWN OF EXISTING SYSTEMS SHALL BE COORDINATED AND PLANNED WITH THE CONTRACTING OFFICER PRIOR TO THE START OF CONSTRUCTION.
- CONTRACTOR SHALL PROVIDE TEST AND BALANCE OF SYSTEMS AFTER WORK IS COMPLETED. AIRFLOW AND WATER FLOW VALUES SHALL BE RETURNED TO NEW VALUES WHERE SHOWN ON PLANS AND TO PRE-DEMOLITION RECORDED VALUES WHERE NEW VALUES ARE NOT SHOWN.
- THE CONTRACTOR SHALL SEISMICALLY BRACE ALL EXISTING AND NEW NON STRUCTURAL ELEMENTS FALLING WITHIN RENOVATION LIMITS OF CONSTRUCTION" AS REQUIRED BY CODE. REFER TO SPECIFICATION SECTION 130541 (SEISMIC RESTRAINT REQUIREMENTS FOR NON-STRUCTURAL COMPONENTS) FOR ADDITIONAL INSTRUCTIONS.

### MECHANICAL SHEET INDEX

MH-001	MECHANICAL COVER SHEET
MD-101	MECHANICAL DEMOLITION PLAN
MD-102	MECHANICAL PHASING PLAN
MH-101	MECHANICAL FLOOR PLAN
MH-401	MECHANICAL SCHEDULES
MH-501	MECHANICAL DETAILS

### APPLICABLE CODES & MANUALS

VA MASTER SPECIFICATIONS PG-18-1
VA DESIGN AND CONSTRUCTION PROCEDURES PG-18-3
VA SEISMIC DESIGN REQUIREMENTS H-18-8
VA HVAC DESIGN MANUAL PG-18-10
VENTILATION FOR ACCEPTABLE INDOOR AIR QUALITY - ASHRAE STANDARD 62.1-2004
INTERNATIONAL BUILDING CODE - 2018 (IBC) AND REFERENCED FAMILY OF CODES (MC, IECC, IFG AND IPC)
CDC GUIDANCE FOR ENVIRONMENTAL INFECTION CONTROL IN HEALTHCARE FACILITIES (PER HICPAC)




## CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS		
NO.	DESCRIPTION	DATE

CONSULTANT

ARCHITECT/ENGINEER OF RECORD
A/E: <b>RGD</b> CONSULTING ENGINEERS JUPITER   ORLANDO 561-743-0165   407-845-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #1230, ORLANDO, FL 32811 CERT OF AUTH 5454




FMS Project and Section  VA U.S. Department of Veterans Affairs
--

Drawing Title <b>MECHANICAL COVER SHEET</b>
Approved:

Phase CD(100%CD-ISSUE FOR BID)
FULLY SPRINKLERED


Project Title VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS
Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201
Issue Date 04/22/2024
Checked RSM
Drawn P/JG

Project Number 672-22-810
Building Number 1
Drawing Number MH-001




KEYNOTE LEGEND	
DE02	DUCTWORK TO BE CAPPED.
DE04	EXHAUST AIR GRILLE TO BE RELOCATED. REFER TO SHEET MD-102 FOR NEW LOCATION.

Mechanical Demolition Floor Plan - HLD  
SPS  
1/2" = 1'-0"




CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD	STAMP	FMS Project and Section	Drawing Title		Phase	Project Title	Project Number																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
NO.	DESCRIPTION	DATE					MECHANICAL DEMOLITION PLAN				CD(100%CD-ISSUE FOR BID)	VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS	672-22-810																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																												
				<div><div>A/E:</div><div><div><div>RGD</div><div>CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-743-0165   407-845-6630 WWW.RGDENGINEERS.COM</div></div><div><div>121 S ORANGE AVE #1230, ORLANDO, FL 32811</div><div>CERT OF AUTH 5454</div></div></div></div>	<div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div><div><div></div></div></div><div>LIC. 24629 EXPIRA</div><div>PUERTO RICO</div></div>																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				



KEYNOTE LEGEND	
ME01	CONNECT TO EXISTING DUCTWORK SYSTEM.
ME04	PROVIDE PORTABLE AIR SCRUBBER DURING INTERIM CONSTRUCTION PHASE WITH HEPA FILTER. CONNECT TO EXHAUST SYSTEM WITH FLEXIBLE DUCT AND LOCKING COLLAR. PROVIDE WITH CORRUGATED ALUMINUM FLEXIBLE DUCTWORK. CAP DUCTWORK CONNECTION POST INTERIM CONSTRUCTION PHASE. BASIS OF DESIGN MODEL: PREDATOR PORTABLE AIR SCRUBBER PRED1200.

Mechanical Demolition Phase - Floor Plan -  
HLD SPS  
1/2" = 1'-0"



CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS		
NO.	DESCRIPTION	DATE

CONSULTANT

ARCHITECT/ENGINEER OF RECORD
A/E: <b>RGD</b> CONSULTING ENGINEERS JUPITER   ORLANDO 561-743-0165   407-845-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE, #1230, ORLANDO, FL 32811 CERT OF AUTH 5454

STAMP


FMS Project and Section
U.S. Department of Veterans Affairs

Drawing Title
MECHANICAL PHASING PLAN
Approved:


Phase
CD(100%CD-ISSUE FOR BID)
FULLY SPRINKLERED

Project Title
VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS
Location
10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201
Issue Date
04/22/2024
Checked
RSM
Drawn
PJG

Project Number
672-22-810
Building Number
1
Drawing Number
MD-102




KEYNOTE LEGEND	
ME01	CONNECT TO EXISTING DUCTWORK SYSTEM.
ME02	PROVIDE NEW 4" ROUND DUCT TO NEW PASS-THRU AER EQUIPMENT. SLOPE DUCTWORK TOWARDS NEW AER EQUIPMENT. REFER TO MANUFACTURER'S INSTALLATION GUIDELINES FOR CONNECTION INFORMATION.
ME05	PROVIDE MANUAL ROOM PRESSURE MONITOR. BASIS OF DESIGN: AIRFLOW DIRECTION - BALL-IN-THE-WALL.



1 Mechanical Floor Plan - HLD SPS  
1/2" = 1'-0"

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD	STAMP	FMS Project and Section	Drawing Title		Phase	Project Title	Project Number	
NO.	DESCRIPTION	DATE					MECHANICAL FLOOR PLAN				CD(100%CD-ISSUE FOR BID)	VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS
				<div>A/E:<div><div>RGD CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-743-5088   407-565-6600 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #1200, ORLANDO, FL 32811 CERT OF AUTH 5454</div></div></div>	<div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div></div><div>LIC. 24809 EXPIRA</div><div>PUERTO RICO</div></div>							
							Approved:		FULLY SPRINKLERED	Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201	Drawing Number	
										Issue Date	Checked	Drawn
										04/22/2024	RSM	PJG
											MH-101	

4/22/2024 11:07:16 AM

VA FORM 08-6231

**F**

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

Project Number 672-22-810
Building Number 1
Drawing Number MH-401

A

B

C

D

E

F

A


B

C

D

E

F




- NOTE:
- ALL VANE ELBOWS SHALL BE CONSTRUCTED AND INSTALLED AS DETAILED BY SMACNA.
  - WHEN W1 DOES NOT EQUAL W2, VANE SHALL BE SINGLE THICKNESS VANE TYPE REGARDLESS OF W DIMENSION.
  - ALL SINGLE THICKNESS VANES SHALL HAVE A 2" [50mm] RADIUS, 1 1/2" [40mm] MAXIMUM SPACE BETWEEN VANES AND A 3/4" [20mm] TRAILING EDGE.
  - WHEN W EQUALS W2 AND W1 IS GREATER THAN 20" [500mm] VANES SHALL BE DOUBLE VANE TYPE.

1

DUCTWORK SQUARE VANE ELBOWS

NTS



4

SUPPLY DUCT TAKEOFF - AIR TERMINAL UNIT

NTS

LOAD RATED FASTENERS

BAND OF SAME SIZE AS HANGER STRAP

50" [1250mm] Ø & UNDER

HANGER RODS

BAND

OVER 50" [1250mm] Ø


MAX. DUCT IN. [mm]	QUANTITY/SIZE IN. [mm]	MAX. LOAD LBS. [kg]	MAX. SPACING IN. [mm]
26 [650]	ONE 1 [25] x 22 GA STRAP	260 [119]	144 [3600]
36 [900]	ONE 1 [25] x 18 GA STRAP	420 [190]	144 [3600]
50 [1250]	ONE 1 [25] x 16 GA STRAP	700 [317]	144 [3600]
60 [1500]	TWO 3/8 [10] RODS	1320 [598]	144 [3600]
84 [2100]	TWO 1/2 [13] RODS	2900 [1133]	144 [3600]

NOTE:  
TABULATED DATA FROM SMACNA  
ALLOWS FOR DUCT REINFORCING AND INSULATION, BUT NO EXTERNAL LOAD.

7

ROUND DUCT HANGERS

NTS




- NOTE:
- THE INTERIOR SURFACE OF ALL RADIUS ELBOWS SHALL BE MADE ROUND.
  - ALL STANDARD RADIUS ELBOWS CAN BE SUBSTITUTED WITH SHORT RADIUS ELBOWS. ALL SHORT RADIUS ELBOWS SHALL HAVE VANES. VANES SHALL BE CONSTRUCTED, SUPPORTED AND FASTENED AS RECOMMENDED BY SMACNA.

2

DUCTWORK RADIUS ELBOWS


NTS



5

ALTERNATE SUPPLY DUCT TAKEOFF - AIR TERMINAL UNITS


NTS



9

FLEXIBLE AIR DUCT CONNECTOR

NTS




3

SUPPLY DUCTWORK TAKE-OFFS

NTS


- DESIGNER'S NOTES:
- THE SUPPLY REGISTER TAKE-OFF MAY BE USED FOR UP TO 25% OF THE MAIN DUCT CFM. THE BRANCH DUCT TAKE-OFF MAY BE USED FOR UP TO 15% OF THE MAIN DUCT CFM ANYTIME AND UP TO 40% WHEN THE MAIN DUCT VELOCITY IS 1000 FPM [5.1 M/S] OR LESS. THE AIR SPLIT DUCT TAKE-OFF SHALL BE USED IN ALL OTHER CASES AND MAY BE USED AT ANYTIME.
  - SHOW ALL VOLUME DAMPERS ON FLOOR PLANS.



6

EXHAUST OR RETURN BRANCH DUCTWORK

NTS



- NOTE:
- DELETE INSULATION STAND-OFF ON DUCTWORK WITHOUT EXTERIOR INSULATION.
  - DETAIL SHOWS SINGLE BLADE DAMPER. DAMPER INSTALLATION SHALL BE SIMILAR FOR MULTI-BLADE DAMPERS & ROUND DAMPERS.

10

VOLUME DAMPER DETAIL

NTS

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD	STAMP	FMS Project and Section	Drawing Title	Phase	Project Title	Project Number
NO.	DESCRIPTION	DATE								
							MECHANICAL DETAILS	CD(100%CD-ISSUE FOR BID)	VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS	672-22-810
										Building Number
										1
									Location	10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201
								FULLY SPRINKLERED	Issue Date	04/22/2024
									Checked	RSM
									Drawn	PJG
										Drawing Number
										MH-501

## GENERAL PLUMBING NOTES


- ALL WORKSMANSHIP AND MATERIALS SHALL BE IN STRICT ACCORDANCE WITH APPLICABLE CODES AS SHOWN.
2. THE PLUMBING CONTRACTOR SHALL BE HELD TO HAVE VERIFIED ALL EXISTING CONDITIONS, INCLUDING SITE VISITATION, AND REVIEW OF AS BUILT DOCUMENTATION AS APPLICABLE PRIOR TO BIDDING, ORDERING, FABRICATION OR INSTALLATION OF ANY MATERIALS OR EQUIPMENT ON THIS PROJECT.
3. UNLESS OTHERWISE SPECIFIED, ALL MATERIALS SHALL BE NEW. ALL WORK SHALL BE PERFORMED BY A LICENSED PLUMBING CONTRACTOR IN A FIRST CLASS WORKMANLIKE MANNER. THE COMPLETED SYSTEM SHALL BE FULLY TESTED TO MEET ALL EXCAVATION AND BACK FILL AS REQUIRED FOR THIS PHASE OF CONSTRUCTION SHALL BE A PART OF THIS CONTRACT.
4. REQUIRED INSURANCE SHALL BE PROVIDED BY THE PLUMBING CONTRACTOR FOR PROTECTION AGAINST PUBLIC LIABILITY AND PROPERTY DAMAGE FOR THE DURATION OF THE WORK.
5. PLUMBING CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS, FEES, INSPECTION AND TESTS. PLUMBING CONTRACTOR TO OBTAIN PERMIT AND APPROVED SUBMITTALS PRIOR TO BEGINNING WORK OR ORDERING EQUIPMENT. PLUMBING CONTRACTOR MUST BE PRESENT FOR ALL INSPECTIONS OF HIS WORK BY REGULATORY AUTHORITIES.
6. DRAWINGS ARE DIAGRAMMATIC IN NATURE AND ARE TO BE READ IN CONJUNCTION WITH ARCHITECTURAL, MECHANICAL, ELECTRICAL AND STRUCTURAL DRAWINGS AND ARE CONSIDERED TO BE ONE SET OF DOCUMENTS. BENDS OFFSETS AND FITTINGS WILL BE THE CONTRACTOR'S RESPONSIBILITY AND SHALL BE PROVIDED TO ARCHITECT AND ENGINEER FOR REVIEW PRIOR TO SUBMITTING FINAL BID. CONTRACTOR SHALL MAKE HIMSELF AVAILABLE FOR REVIEWING DOCUMENTS WITH ARCHITECT/ENGINEER UPON REQUEST.
7. CONTRACTOR SHALL SUBMIT FOR APPROVAL ELECTRONIC PDF COPIES OF MANUFACTURER DRAWINGS FOR ALL PLUMBING FIXTURES AND EQUIPMENT INCLUDED IN CONTRACT. ALL MATERIAL SHALL BE NEW FROM A U.S. MANUFACTURER OF GOOD QUALITY. ALL WORK SHALL BE PERFORMED IN A WORKMANLIKE MANNER BY SKILLED TRADESMEN.
8. GENERAL CONTRACTOR SHALL CONSIDER THE PROJECT AS ONE SET OF DOCUMENTS. GENERAL CONTRACTOR SHALL PROVIDE AN ENTIRE SET OF DOCUMENTS SHOWING ALL TRADES TO EACH SUBCONTRACTOR PRIOR TO BIDDING AND CONSTRUCTION. GENERAL CONTRACTOR SHALL COORDINATE WITH ALL OTHER CONTRACTORS TO INFORM ARCHITECT/ENGINEER OF ANY CONFLICTS ON THE DOCUMENTS PRIOR TO SUBMITTING FINAL BID AND COMMENCING ANY WORK. CONTRACTOR SHALL MAKE HIMSELF AVAILABLE FOR REVIEWING DOCUMENTS WITH ARCHITECT/ENGINEER UPON REQUEST.
9. THE GENERAL CONTRACTOR SHALL PROVIDE IN WRITING ON COMPANY LETTER HEAD ALL ITEMS VALUE ENGINEERED OR OMITTED FROM ENTIRE PROJECT. THIS DOCUMENT SHALL HAVE DETAILED DESCRIPTION AND TRANSPARENCY OF ALL ITEMS. EACH DISCREPANCY AND DISCREPANCY TO VERIFY EXISTING INVERT ELEVATIONS. THE CONTRACTOR SHALL REPORT WATER DISTRIBUTION PIPING SHALL BE TYPE EITHER "L" COPPER FOR NON CRITICAL WATER SYSTEMS, CRITICAL WATER DISTRIBUTION PIPING TO BE SCH 40 STAINLESS STEEL WITH BUTT-WELDED OR GROOVED FITTINGS.
10. ALL WORK SHALL BE COORDINATED WITH OTHER TRADES TO AVOID INTERFERENCE WITH THE PROGRESS OF CONSTRUCTION. REPORT ANY DISCREPANCY TO ENGINEER/ARCHITECT PRIOR TO BEGINNING CONSTRUCTION.
11. VERIFY LOCATION, SIZE, DIRECTION OF FLOW AND INVERTS OF ALL EXISTING UTILITIES PRIOR TO BEGINNING OF CONSTRUCTION. ADVISE ENGINEER OF ANY DISCREPANCIES.
12. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING THE INVERT ELEVATIONS OF EXISTING DRAINAGE PIPING AS REQUIRED TO ASSURE THAT CONNECTIONS TO EXISTING SYSTEMS CAN BE COMPLETED. THE CONTRACTOR SHALL SCOPE, EXCAVATE AND REPAIR ANY VARYING EXISTING INVERT ELEVATIONS. THE CONTRACTOR SHALL REPORT ANY DISCREPANCIES TO THE ENGINEER IN WRITING PRIOR TO COMMENCEMENT OF THE GROUND ROUGH.
13. WATER DISTRIBUTION PIPING SHALL BE TYPE EITHER "L" COPPER FOR NON CRITICAL WATER SYSTEMS, CRITICAL WATER DISTRIBUTION PIPING TO BE SCH 40 STAINLESS STEEL WITH BUTT-WELDED OR GROOVED FITTINGS.
14. UNLESS OTHERWISE INDICATED ON THE PLAN, THE SOIL WASTE PIPING SHALL BE CAST IRON ABOVE AND BELOW SLAB.
15. ALL FIXTURES MUST BE PROVIDED WITH READILY ACCESSIBLE STOPS AND APPROPRIATELY MARKED ACCESS PANELS. ISOLATION VALVES LOCATED IN CEILING CAVITIES ABOVE HARD CEILINGS SHALL BE SUPPLIED WITH APPROVED ACCESS PANELS. COORDINATE LOCATIONS WITH GENERAL CONTRACTOR PRIOR TO INSTALLATION. ALL VALVES TO BE LOCATED NO MORE THAN 24" ABOVE THE ACCESS PANEL.
16. FURNISH AND INSTALL APPROVED, ENGINEERED PISTON TYPE MECHANICAL WATER HAMMER ARRESTORS AT EACH PLUMBING FIXTURE OR FIXTURE GROUP WITH QUICK CLOSING VALVES. INSTALLATION OF THE ARRESTOR SHALL BE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS AND SHALL BE IN COMPLIANCE WITH IBC-P-604 AND ASSE 1010. THE ARRESTOR SHALL BE LOCATED WITHIN THE EFFECTIVE RANGE OF THE QUICK CLOSING VALVE, WITH ACCESS UNLESS THE ARRESTOR IS DESIGNED FOR CONCEALED APPLICATION AND IS APPROVED BY AHJ.
17. DIELECTRIC COUPLINGS ARE REQUIRED BETWEEN ALL DISSIMILAR METAL IN PIPING AND EQUIPMENT CONNECTIONS.
18. ISOLATE COPPER PIPE FROM HANGER OR SUPPORTS WITH ISOLATOR PAD.
19. ALL FIRE RATED FLOOR AND WALL PENETRATIONS SHALL BE PROPERLY PROTECTED FROM FIRE, SMOKE AND WATER PENETRATION BY FILLING VOIDS BETWEEN PIPE AND WALL/FLOOR SLEEVES WITH FIRE RATED FOAM, TO ACHIEVE THE SAME RATING AS WALLS OR FLOORS AS PART OF THE PLUMBERS WORK.
20. PLUMBING CONTRACTOR SHALL GUARANTEE ALL MATERIALS AND WORKMANSHIP FREE FROM DEFECTS. CORRECTION OF ANY DEFECTS SHALL BE COMPLETED WITHOUT ADDITIONAL CHARGE AND SHALL INCLUDE REPLACEMENT OR REPAIR OF ANY OTHER PHASE OF THE INSTALLATION WHICH MAY HAVE BEEN DAMAGED.
21. PROVIDE ACCESS PANELS FOR ALL CONCEALED VALVES AND ALL WATER HAMMER ARRESTERS. ACCESS PANELS IN WALLS SHALL BE 12" MINIMUM RATING AND MUST MATCH THE FINISH OF THE WALL IN WHICH IT IS INSTALLED. ALL VALVES AND WATER HAMMER ARRESTER TO BE LOCATED NO MORE THAN 24" ABOVE THE ACCESS PANEL.
22. PROVIDE CHROME PLATED CHROMIUM COVER PLATE AND CLEAN OUT PLUG OR ACCESS PANEL FOR ALL WALL CLEAN OUTS.
23. ALL CONTROL VALVES SHALL BE TAGGED AND MARKED. A REPRODUCIBLE DIAGRAM LOCATING ALL VALVES SHALL BE PROVIDED FOR OPERATOR.
24. PROVIDE ANGLE STOPS ON ALL WATER SERVICE LINES TO FIXTURES FOR INDIVIDUAL SHUT-OFF.
25. REFER TO SPECIFICATION BOOK FOR PIPE INSULATION SPECIFICS.
26. ALL FLOOR DRAINS NOT OTHERWISE PRIMED WITH INDIRECT WASTE SHALL BE PRIMED FROM THE NEAREST DOMESTIC WATER FIXTURE. REFERENCE FLOOR DRAIN PRIMING DETAIL.
27. PLUMBING CONTRACTOR SHALL PROVIDE ENGINEER WITH AS-BUILT DRAWINGS UPON COMPLETION.
28. UNLESS OTHERWISE SPECIFIED, THE PLUMBING CONTRACTOR SHALL PROVIDE MOTOR STARTERS AS REQUIRED FOR ALL PLUMBING RELATED EQUIPMENT. THE STARTERS SHALL BE MATCHED TO THE EQUIPMENT AND THE SERVICE VOLTAGE. PHASE LOSS MONITORS/PROTECTION SHALL BE REQUIRED ALL THREE PHASE EQUIPMENT. COORDINATE PRIOR TO ORDERING/PURCHASING/INSTALLATION.
29. CONTRACTOR SHALL SUBMIT FOR APPROVAL (BEFORE ORDERING OR INSTALLING SUCH UNITS) TO THE MECHANICAL ENGINEER A LISTED LIST OF ALL BACKFLOW PREVENTERS TO BE USED FOR PROJECT.
30. REVERSE OSMOSIS SYSTEMS (RO SYSTEMS) SHALL BE PIPED WITH STAINLESS STEEL.
31. ALL PIPING TO BE TESTED IN ACCORDANCE WITH SECTION 312 OF THE INTERNATIONAL PLUMBING CODE.

## APPLICABLE BUILDING CODES

## ADDITIONAL NOTES

# PLUMBING SHEET INDEX

Project Number 672-22-810
Building Number 1
Drawing Number PL-001



CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

4/22/2024 11:58:59 AM

VA FORM 08 - 6231

REVISIONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD <div>A/E:<div><div>RGD</div><div>CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-743-0165   407-945-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #1230, ORLANDO, FL 32811 CERT OF AUTH 5454</div></div></div>	STAMP <div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div></div><div>LIC 24029 EXPIRA</div><div>PUERTO RICO</div></div>	FMS Project and Section <div>VAU.S. Department of Veterans Affairs</div>	Drawing Title FIRE PROTECTION PLANS		Phase CD(100%CD-ISSUE FOR BID)	Project Title VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS		Project Number 672-22-810	
NO.	DESCRIPTION	DATE					Approved:		Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		Building Number 1		
										Drawing Number PL-101			
						FULLY SPRINKLERED		Issue Date 04/22/2024	Checked RSM	Drawn VMC			

1

2

3

4

5


6

7

8

9

10





KEYNOTES	
1	CONNECT TO EXISTING CRITICAL WATER PIPING ALONG WALL, GC TO VERIFY EXISTING PIPE LOCATIONS, PROVIDE ISOLATION VALVE NEAR CONNECTION POINT
2	CONNECT TO EXISTING DOMESTIC WATER COLD PIPE IN WALL FROM REMOVED EXISTING EYE WASH, GC TO FIELD VERIFY EXACT LOCATION.
3	DISCHARGE CONNECTION FOR THERMOSTATIC MIXING VALVE SETUP AND PURGE. ROUTE IN CEILING SPACE WITH 1/4 IN/FT SLOPE AND DISCHARGE TO HUB DRAIN.
4	CONNECT TO EXISTING SANITARY PIPING, GC TO VERIFY EXISTING PIPE LOCATIONS
5	CONNECT TO EXISTING SANITARY VENT PIPING, GC TO VERIFY EXISTING PIPE LOCATIONS
6	HUB DRAIN FOR THERMOSTATIC MIXING VALVE SETUP AND PURGE DISCHARGE.
7	ENSURE 90 PSI AIR PRESSURE IS PROVIDED FOR EQUIPMENT OPERATIONS.
8	THERMOSTATIC MIXING VALVE TO BE SET FOR AN OUTPUT TEMPERATURE OF 96°F.

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024


4/22/2024 11:56:01 AM

VA FORM 08 - 6231

<div>REVISIONS</div> <table><tr><th>NO.</th><th>DESCRIPTION</th><th>DATE</th></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr></table>			NO.	DESCRIPTION	DATE																						<div>CONSULTANT</div> <div> </div>	<div>A/E:<div>RGD<div>CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-743-0165   407-845-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #1230, ORLANDO, FL 32811 CERT OF AUTH 5454</div></div></div>	<div>ARCHITECT/ENGINEER OF RECORD</div> <div> </div>	<div>STAMP</div> <div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div></div><div>LIC. 24629 EXPIRA</div><div>PUERTO RICO</div></div>	<div>FMS Project and Section</div> <div>VAU.S. Department of Veterans Affairs</div>	<div>Drawing Title</div> <div>PLUMBING PLANS</div>	<div>Phase</div> <div>CD(100%CD-ISSUE FOR BID)</div>	<div>Project Title</div> <div>VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS</div>	<div>Project Number</div> <div>672-22-810</div>
NO.	DESCRIPTION	DATE																																	
						<div>Approved:</div> <div> </div>	<div>FULLY SPRINKLERED</div>	<div>Location</div> <div>10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201</div>	<div>Building Number</div> <div>1</div>	<div>Drawing Number</div> <div>PL-201</div>																									
								<div>Issue Date</div> <div>04/22/2024</div>	<div>Checked</div> <div>RSM</div>	<div>Drawn</div> <div>VMC</div>																									
1	2	3	4	5	6	7	8	9	10																										



- NOTES:
1. WATER QUALITY TEST PORT.
  2. THERMOSTATIC MIXING VALVE TO BE SET FOR 96F WATER TEMPERATURE.
  3. CONNECTION FOR TMV SETUP AND PURGE.



- ## GENERAL NOTES:
1. ALL SPRINKLER WORK SHALL BE DONE AND TESTED IN ACCORDANCE WITH NFPA # 13, (LATEST EDITION), FACTORY MUTUAL, OSHA, OWNER UNDERWRITER, LOCAL BUILDING CODE AND ALL AUTHORITIES HAVING JURISDICTION.
  2. ALL SPRINKLER PIPING SHALL BE CARBON STEEL, BLACK, SCHEDULE 40 ASTM A-53 WITH SCREWED CAST IRON 125 # FITTINGS OR GROOVE TYPE JOINT.
  3. CONTRACT DOCUMENTS FOR THE PROJECT (DRAWINGS AND SPECIFICATIONS) CONSTITUTE THE GENERAL REQUIREMENTS FOR THE PROJECT FIRE PROTECTION SPRINKLER SYSTEM. SUCH CONTRACT DOCUMENTS SHOW THE GENERAL CONCEPT AND DESIGN CRITERIA OF THE DESIGN; IT SHALL BE THE FIRE PROTECTION CONTRACTOR/DESIGNER RESPONSIBILITY TO PREPARE A SYSTEM DESIGN AND FABRICATION DRAWINGS FOR APPROVAL IN COMPLIANCE WITH SUCH REQUIREMENTS. IT IS THE INTENT OF THE CONTRACT DOCUMENTS TO SUBSTITUTE AND/OR WAIVE THE TOTAL RESPONSIBILITY OF THE CONTRACTOR/DESIGNER FOR THE SYSTEM DESIGN AS REQUIRED HEREIN. IT SHALL BE THE DESIGNER/FABRICATOR RESPONSIBILITY TO SUBMIT TO THE SPRINKLER AUTHORITY/LOCAL BUILDING JURISDICTION FOR REVIEW AND APPROVAL. IT SHALL BE THE CONTRACTOR/DESIGNER RESPONSIBILITY TO COORDINATE THE ENTIRE SYSTEM DESIGN/INSTALLATION WITH ALL BUILDING STRUCTURES; DUCTS, DIFFUSERS AND FANS; PIPING AND PIPING APPURTENANCES; ELECTRICAL CONDUITS, LIGHTS, VENTILATION, AND ALL ELECTRICAL DEVICES AND APPURTENANCES; GENERAL BUILDING COMPONENTS; ETC. THAT MAY AFFECT THE SPRINKLER SYSTEM DESIGN AND/OR INSTALLATION.
  4. FLUSHING CONN. SHALL BE PROVIDED AT THE END OF EACH CROSS/FEED MAIN, CONSISTING OF A 4 IN LONG BY 2 IN DIAM. NIPPLE WITH SCREW CAP FITTING.
  5. ALL MAIN (S) BRANCH LINES OUTLETS TO BE SHOP WELDED IN ACCORDANCE W/ NFPA 13, (LATEST EDITION.)
  6. NEW SEISMIC BRACINGS SHALL BE PROVIDED TO EXISTING SYSTEM IF NOT PROVIDED @ SUCH LOCATION.
  7. EARTHQUAKE BRACING CALCULATIONS SHALL BE BASED ON:  
 \*SEISMIC COEFFICIENT  $C_p=0.75$   
 \*ZONE OF INFLUENCE METHOD



- LEGEND:
- ↓ NEW CROSS MAIN (30"—0" MAX. FOR 3" PIPE) LATERAL BRACING
- ↘ NEW CROSS MAIN (50"—0" MAX. FOR 3" PIPE) LONGITUDINAL BRACING
- NEW PIPE HANGER

PIPE HANGER AND BRACING AS  
BASIS OF DESIGN SHOWN.  
PLEASE PROVIDE EQUAL OR  
EQUIVALENT.

## APPENDIX C

## PRE-SITE REQUIREMENTS CHECKLIST

INITIAL AND SIGN AT THE TIME OF PRE-SITE INSPECTION

Inspection Item	Description	Initials
Wall Preparation	<p>Wall opening meets specification for the number of reproprocessors</p> <p>Facility connections are in the proper locations and are accessible</p> <p>Openings in underside of the wall are the proper size and in the proper locations</p>	
Water Supply	<p>1/2" (13 mm) NPT female connection with shutoff valve and pressure gauge</p> <p>Potable or RO water filtered to 1 micron</p> <p>Pressure of 40 to 87 psi (3 to 6 bar) (dynamic pressure)</p> <p>Minimum flow rate of 2.6 gal/min (10 l/min) (dynamic)</p> <p>Supplied water temperature 95°F ± 4°F (35°C ± 2°C)</p> <p>Water supply need dedicated drain for bypass valve</p>	
Drain	<p>Floor drain meets requirements and is installed in the proper location</p> <p>Capable of draining 10.5 gal/min (40 l/min)</p>	
Air Supply	<p>1/4" (6 mm) NPT female connection with shutoff valve and pressure gauge</p> <p>Pressure of 58 to 145 psi (4 to 10 bar)</p> <p>The demand of compressed air is 1.1 scfm (32 l/min ANR)</p> <p>Air dry and oil free per specifications</p> <p>Filtered to 5 microns</p>	
Electrical Supply	<p>120 VAC ±10%, single phase, 60 Hz, 1200 Watts</p> <p>GFI protected NEMA 5-15R receptacle</p>	
Ventilation	<p>Minimum of 10 room air exchanges per hour</p> <p>4" (100 mm) round duct</p> <p>A minimum of 25 cfm (12 l/s) at 0.25 inches (6 mm)-water (62 PA) static pressure at duct</p>	
Network	<p>RJ45 receptacle</p> <p>Internet access</p>	
Customer Site		
Customer Representative Signature	Date	Title Email
Serial #		
Serial #		
Serial #		
Serial #		
Serial #		



PLUMBING SCHEDULE							
MARK	ITEM	MANUFACTURER	DESCRIPTION	RIM HEIGHT (AFF)	MOUNTING	TRIM / ACCESSORIES	NOTES
FS-1	FLOOR SINK	ZURN	Z1750ZM	FLUSH	FLOOR MOUNTED	12" X 12" X 6" DEEP, 16 GAGE, ALL TYPE 316 STAINLESS STEEL LIGHT-DUTY SANI-FLOOR RECEPTOR WITH NON-TILT, LOOSE SET FULL GRATE WITH 1/2" SQUARE OPENINGS AND ANTI-SPLASH STAINLESS STEEL INTERIOR DOME STRAINER,	-
TMV-1	THERMOSTATIC MIXING VALVE	WATTS	LFL1170 - 1/2"	-	-	SET THERMOSTATIC MIXING VALVE TO 95 DEG F.	-
NOTES:							

[illegible]

	CONSULTANT

ARCHITECT/ENGINEER OF RECORD

A/E:

**RGD**  
CONSULTING  
ENGINEERS

JUPITER ORLANDO  
561-743-0165 / 407-845-8630  
WWW.RGDENGINEERS.COM

121 S ORANGE AVE #1230, ORLANDO, FL 32811

STAMP

ROBERT G DAVENPORT  
INGENIERO  
LICENCIADO  
LIC. 24629  
EXPIRA  
PUERTO RICO

**FMS**  
**Project and**  
**Section**

**VA** | U.S. Department of  
Veterans Affairs

Drawing Title	
PLUMBING DETAILS AND SCHEDULES	
Approved:	

Phase

CD(100%CD-ISSUE FOR BID)

FULLY SPRINKLERED

Project Title <b>VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS</b>		
Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		
Issue Date 04/23/2024	Checked RSM	Drawn VMC


Project Number 672-22-810
Building Number 1
Drawing Number PL-501

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

## ELECTRICAL NOTES

- [illegible]

## ELECTRICAL SYMBOL LEGEND



NOTE: NOT ALL SYMBOLS MAY APPLY TO PLANS








## ELECTRICAL ABBREVIATIONS

AC	- AMPERE	MCA	- MINIMUM CIRCUIT AMPACITY
AC	- ALTERNATING CURRENT	MCB	- MAIN CIRCUIT BREAKER
AF	- AMP FRAME	MCC	- MOTOR CONTROL CENTER
AHJ	- ABOVE FINISHED FLOOR	MFR	- MANUFACTURER
AUF	- AUTHORITY HAVING JURISDICTION	+ MH	- MOUNTING HEIGHT
AL	- ALUMINUM	ML	- MAIN LUGS ONLY
ATS	- AUTOMATIC TRANSFER SWITCH	MO, MOCP	- MAXIMUM OVERCURRENT PROTECTION
BR	- BREAKER	MSB	- MAIN SWITCHBOARD
BRKR	- BREAKER	MTS	- MANUAL TRANSFER SWITCH
C or COND	- CONDUIT	MW	- MICROWAVE
CD	- CANCELLED	NEC	- NATIONAL ELECTRICAL CODE
CKT	- CIRCUIT	(N)	- NONE
CT	- CURRENT TRANSFORMER	NA	- NOT APPLICABLE
CU	- COPPER	NC	- NORMALLY CLOSED
DN	- DOWN	NF	- NOT FUSED
DW	- DISHWASHER	NI	- NOT IN CONTACT
DWG	- DRAWING	NO	- NORMALLY OPEN
DC	- DIRECT CURRENT	OCPP	- OVERCURRENT PROTECTION DEVICE
E or EXIST	- EXISTING	P	- POLE
E.C	- ELECTRICAL CONTRACTOR	PH or O	- PHASE
ELEV	- ELEVATOR	NEMA	- NATIONAL ELECTRIC MANUFACTURERS ASSOCIATION
EMER	- EMERGENCY		
EMT	- ELECTRIC METALLIC TUBING	PB	- PULL BOX
EUH	- ELECTRIC UNIT HEATER	PH	- PHOTO LITHOGRAPHY
EW	- ELECTRIC WATER COOLER	PNL	- PANEL BOARD
EWH	- ELECTRIC WATER HEATER	R	- RELOCATED
F	- FUSE	RE	- RANGE OVEN
FA	- FIRE ALARM	RECEPT	- RECEPTACLE
FCA	- FAULT CURRENT AVAILABLE	REF	- REFRIGERATOR
FCR	- FAULT CURRENT RATING	RM	- ROOM
C, GND	- GROUND	RP	- SURFACE PROTECTIVE DEVICE
GD	- GARBAGE DISPOSAL	THD	- TOTAL HARMONIC DISTORTION
GFIFGFCI	- GROUND FAULT CIRCUIT INTERRUPTER	TVSS	- TRANSIENT VOLTAGE SURGE SUPPRESSION
GFCI	- GROUND FAULT EQUIPMENT PROTECTION	UL	- LISTED
HZ	- HERTZ	UL	- UNDERWRITERS LABORATORIES
H	- HORSEPOWER	UCN	- UNLESS OTHERWISE NOTED
J	- JUNCTION BOX	UPS	- UNINTERRUPTIBLE POWER SUPPLY
JA	- JUNCTION BOX	V	- VOLT
KVA	- KILOWATT-AMPERE	VFD	- VARIABLE FREQUENCY DRIVE
KW	- KILOWATT	W	- WATT
LTG	- LIGHTING	WP	- WEATHERPROOF
M	- METER	XFRM	- TRANSFORMER

## ELECTRICAL SHEET INDEX


E-001	ELECTRICAL COVER SHEET
EP-101	ELECTRICAL FLOOR PLANS
E-501	ELECTRICAL DETAILS
E-601	PANEL SCHEDULES

### LOW VOLTAGE LEGEND

- |   |  |
|---|--|
|  | DATA OUTLET WITH 1" CONDUIT STUBBED OUT FROM WALL 6" ABOVE CEILING UNLESS OTHERWISE NOTED.   |
|  | DATA OUTLET FLOOR RECESS WITH 1" CONDUIT STUBBED UP TO NEAREST WALL UNLESS OTHERWISE NOTED.  |
|  | CEILING-MOUNTED SPEAKER - IN AREAS OF INACCESSIBLE CEILING, PROVIDE JUNCTION BOX AND 3/4" CONDUIT TO NEAREST ACCESSIBLE CEILING.               |
|  | CEILING-MOUNTED WIRELESS ACCESS POINT - IN AREAS OF INACCESSIBLE CEILING, PROVIDE JUNCTION BOX AND 3/4" CONDUIT TO NEAREST ACCESSIBLE CEILING. |
|  | TELECOM PLYWOOD BACKBOARD. SIZE AS SHOWN ON PLANS.   |
|  | CARD READER WITH 1" CONDUIT STUBBED OUT FROM WALL 6" ABOVE CEILING UNLESS OTHERWISE NOTED.   |
|  | PUSH TO EXIT BUTTON WITH 1" CONDUIT STUBBED OUT FROM WALL 6" ABOVE CEILING UNLESS OTHERWISE NOTED.   |

NOTE: NOT ALL SYMBOLS MAY APPLY TO PLANS

## CIRCUITING LEGEND



## APPLICABLE BUILDING CODES


UNIFORM FEDERAL ACCESSIBILITY STANDARDS, LATEST EDITION.
INTERNATIONAL BUILDING CODE 2021.
VA FIRE PROTECTION DESIGN MANUAL 2011 EDITION.
NFPA 70, NATIONAL ELECTRICAL CODE 2020 EDITION.
NFPA 101, LIFE SAFETY CODE 2019 EDITION.

## ELECTRICAL LEGEND

— NEW WORK.


— — — EXISTING TO BE REMOVED (DEMO)

— EXISTING TO REMAIN.



CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024


REVISIONS			CONSULTANT		ARCHITECT/ENGINEER OF RECORD		STAMP		Drawing Title ELECTRICAL COVER SHEET		Phase CD(100%CD-ISSUE FOR BID)		Project Title VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS		Project Number 672-22-810	
NO.	DESCRIPTION	DATE			A/E:  JUPITER   ORLANDO 561-743-0195   407-845-9930 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #120, ORLANDO, FL 32811 CERT OF AUTH 6454		<b>FMS Project and Section</b>  <b>VA</b> U.S. Department of Veterans Affairs		Approved:				Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		Building Number 1	
										FULLY SPRINKLERED		Issue Date 04/22/2024		Checked RGD	Drawn CDH	E-001




1 ELECTRICAL DEMOLITION FLOOR PLAN  
1/4" = 1'-0"

2 ELECTRICAL NEW WORK FLOOR PLAN  
1/4" = 1'-0"

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD	STAMP	FMS Project and Section	Drawing Title		Phase CD(100%CD-ISSUE FOR BID)	Project Title		Project Number	
NO.	DESCRIPTION	DATE					ELECTRICAL FLOOR PLANS			VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS		672-22-810	
												Building Number 1	
												Drawing Number	
												EP-101	
				<div>A/E:<div><div>RGD CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-743-0168   407-585-6930 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #1230, ORLANDO, FL 32811 CERT OF AUTH 5454</div></div></div>	<div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div></div><div>LIC. 24629 EXPIRA</div><div>PUERTO RICO</div></div>	Approved:		FULLY SPRINKLERED	Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		Drawing Number		
				<div>VAU.S. Department of Veterans Affairs</div>			Issue Date		Checked	Drawn	EP-101		
							04/22/2024		MDB	CDH			



Project Number 672-22-810
Building Number 1
Drawing Number E-501

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

A

B

C

D

E

F

A

B

C

D

E

F

BRANCH PANEL: 1LSPD1																	
Location: Fed From: Mounting: RECESSED						Volts: 120/208 V Phases: 3 Wires: 4				A.I.C. Rating: 22,000 Bus: 500 A M.L.O. / M.C.B.: MCB Feed Thru Lugs:							
CKT	Circuit Description	WIRE	COND	BKR	P	A		B		C		P	BKR	COND	WIRE	Circuit Description	CKT
1	DECO DENTAL WASHER	--	--	20 A	1	0.00	0.00					2	30 A	--	--	RINSE DRYER 2	2
3	SPARE	--	--	20 A	1			0.00	0.00			--	--	--	--		4
5	RINSE DRYER 1	--	--	30 A	2					0.00	0.80	1	20 A	3/4"	2-#12 1-#12G	PASS THUR*	6
7	--	--	--	--	--	0.00	0.80					1	20 A	3/4"	2-#12 1-#12G	PASS THRU*	8
9	ULTRA SONIC 1	--	--	20 A	2			0.00	0.00			2	60 A	--	--	WI	10
11	--	--	--	--	--					0.00	0.00	--	--	--	--		12
13	STERRAD STERILIZER 4	--	--	30 A	3	0.00	0.00					3	30 A	--	--	WASHER STERILIZER	14
15	--	--	--	--	--			0.00	0.00			--	--	--	--		16
17	--	--	--	--	--					0.00	0.00	--	--	--	--		18
19	SPACE	--	--	--	1	--	0.00					3	30 A	--	--	STERRAD STERILIXER 8	20
21	STERRADNX 9	--	--	20 A	1			0.00	0.00			--	--	--	--		22
23	AUTOCLAVE	--	--	20 A	1					0.00	0.00	--	--	--	--		24
25	ULTRA SONIC 2	--	--	20 A	2	0.00	1.00					3	100 A	--	--	1LSPD2	26
27	--	--	--	--	--					0.00	0.86	--	--	--	--		28
29	AUTOCLAVE	--	--	20 A	1					0.00	3.80	--	--	--	--		30
31	STERRANX 10	--	--	20 A	1	0.00											32
33	EF	--	--	20 A	2			0.00									34
35	--	--	--	--	--					0.00							36
Total Load:						1.80 kVA		0.86 kVA		4.60 kVA							
Total Amps:						16 A		7 A		40 A							
Load Classification		Connected Load (kVA)		Demand Factor		Estimated Demand (kVA)						Panel Totals					
Lighting		3.00		100.00%		3.00						Heat or Cool Dominant: Cooling					
Receptacle		4.26		100.00%		4.26						Total Connected Load (kVA): 7.26					
												Total Estimated Demand (kVA): 7.26					
												Total Connected Current: 20 A					
												Total Estimated Demand Current: 7.26					
Note: * INDICATES EXISTING CIRCUIT BREAKER AND NEW INDICATED LOAD. TOTAL CONNECTED CURRENT IS THE ADDITIONA LOAD ADDED TO THE PANEL.																	

BRANCH PANEL: 1LSPD2																	
Location: Fed From: 1LSPD1 Mounting: RECESSED						Volts: 120/208 V Phases: 3 Wires: 4				A.I.C. Rating: 10,000 Bus: 100 A M.L.O. / M.C.B.: MLO Feed Thru Lugs:							
CKT	Circuit Description	WIRE	COND	BKR	P	A		B		C		P	BKR	COND	WIRE	Circuit Description	CKT
1	DECO WOMEN LIGHTS	--	--	20 A	1	0.00	0.00					1	20 A	--	--	PRE SPD CHIEF RECPT	2
3	DECO MENS LIGHTS	--	--	20 A	1			0.00	0.00			1	20 A	--	--	SPD CHIEF CLERK RECPT	4
5	HLD RECPT	--	--	20 A	1					0.00	0.00	1	20 A	--	--	PREPARATION ETO RECPT	6
7	HLD RECPT	--	--	20 A	1	0.00	0.00					1	20 A	--	--	MONITORS FOR ETO	8
9	DESCONTAMINATION RECPT	--	--	20 A	1			0.00	0.00			1	20 A	--	--	COMPUTERIZED AUDIOVISUAL	10
11	DRY AREA RECPT	--	--	20 A	1					0.00	0.00	1	20 A	--	--	TRAINING AREA PROJECTOR	12
13	CHASE CART HAC RECPT	--	--	20 A	1	0.00	0.00					1	20 A	--	--	TRAINING AREA RECPT	14
15	CLEAN MENS LIGHTS	--	--	20 A	1			0.00	0.00			1	20 A	--	--	STAFF LOUNGE REFRIGERATOR	16
17	CLEAN WOMENS LIGHTS	--	--	20 A	1					0.00	0.00	1	20 A	--	--	STAFF LOUNGE RECPT	18
19	CLEAN MACHINE DENTAL HAND	--	--	20 A	1	0.00	0.00					1	20 A	--	--	STAFF LOUNGE HAC RECPT	20
21	POINT GUARD REPEATER	--	--	20 A	1			0.00	0.00			1	20 A	--	--	POINT GUARD REPEATER	22
23	POINT GUARD REPEATER	--	--	20 A	1					0.00	0.00	1	20 A	--	--	ALARM AREA 1-5	24
25	CUSTOM ULTRASONIC	--	--	20 A	1	0.00	0.00					1	20 A	--	--	COMPUTER RECPT	26
27	CUSTOM ULTRASONIC	--	--	20 A	1			0.00	0.00			1	20 A	--	--	UNKNOWN	28
29	UNKNOWN	--	--	20 A	1					0.00	0.00	1	20 A	--	--	UNKNOWN	30
31	UNKNOWN	--	--	20 A	2	0.00	0.00					3	30 A	--	--	UNKNOWN	32
33	--	--	--	--	--			0.00	0.00			--	--	--	--	--	34
35	PASS THRU**	2-#12 1-#12G	3/4"	20 A	1					0.80	0.00	--	--	--	--	--	36
37	SCOPE STORAGE RECPT**	2-#12 1-#12G	3/4"	20 A	1	1.00	--					1	--	--	--	SPACE	38
39	SCOPE STORAGE RECPT**	2-#12 1-#12G	3/4"	20 A	1			0.86	--			1	--	--	--	SPACE	40
41	INSTA-HEAT**	2-#10 1-#10G	3/4"	30 A	1					3.00	--	1	--	--	--	SPACE	42
Total Load:						1.00 kVA	0.86 kVA	3.80 kVA									
Total Amps:						9 A	7 A	32 A									
Load Classification		Connected Load (kVA)		Demand Factor		Estimated Demand (kVA)		Panel Totals									
Lighting		3.00		100.00%		3.00		Heat or Cool Dominant: Cooling									
Receptacle		2.66		100.00%		2.66		Total Connected Load (kVA): 5.66									
								Total Estimated Demand (kVA): 5.66									
								Total Connected Current: 16 A									
								Total Estimated Demand Current: 5.66									
Note: * INDICATES EXISTING CIRCUIT BREAKER AND NEW INDICATED LOAD. ** INDICATES NEW CIRCUIT BREAKER AND INDICATED LOAD. TOTAL CONNECTED CURRENT IS THE ADDITIONA LOAD ADDED TO THE PANEL.																	

CD(100%CD-ISSUE FOR BID) SUBMITTAL - 04/22/2024

REVISIONS			CONSULTANT	ARCHITECT/ENGINEER OF RECORD		STAMP	Drawing Title		Phase	Project Title		Project Number	
NO.	DESCRIPTION	DATE		A/E:	<div><div>RGD CONSULTING ENGINEERS</div><div>JUPITER   ORLANDO 561-743-0165   407-845-6630 WWW.RGDENGINEERS.COM 121 S ORANGE AVE #120, ORLANDO, FL 32811 CERT OF AUTH 5454</div></div>	<div><div>ROBERT G DAVENPORT</div><div>INGENIERO LICENCIADO</div><div>LIC. 24629 EXPIRA</div><div>PUERTO RICO</div></div>	PANEL SCHEDULES			VA PROVIDE HIGH LEVEL DISINFECTION FOR SPS		672-22-810	
							Approved:		FULLY SPRINKLERED	Location 10 CALLE CASIA - ADM. BLDG. SUITE 4M456 SAN JUAN, PR 00921-3201		Building Number	
										Issue Date		1	
										04/22/2024		Drawing Number	
										Checked		E-601	
										MDB			
										CDH			